

FUJITSU

AIRSTAGE™

VRF
Variable Refrigerant Flow System
CATALOGUE
Heat Pump & Heat Recovery

Refrigerant
R410A
INVERTER

for Oceania

FUJITSU GENERAL LIMITED

CREATION OF COMFORT

Fujitsu General's VRF AIRSTAGE™ series has been developed based on years of research and development and expertise in commercial air conditioning solutions. The AIRSTAGE™ series provides high efficiency and reliability for all users, offering air conditioning systems with individual or central control. With a wide range of VRF systems included in the series, there is an AIRSTAGE™ solution available to best meet the needs of any project you are specifying.



Commercial

NEW



Heat Recovery Modular type
for simultaneous heating and cooling operation

AIRSTAGE VR-II

8HP - 48HP 33 models

- Space saving combinations: 8HP to 48HP / 21 models
- Energy efficiency combinations: 16HP to 42HP / 12 models

Page 34~

NEW



Heat Pump Modular type
for heating or cooling operation

AIRSTAGE V-III

8HP - 48HP 33 models

- Space saving combinations: 8HP to 48HP / 21 models
- Energy efficiency combinations: 16HP to 42HP / 12 models

Page 42~



Residential & Light Commercial

NEW



Heat Pump type
for heating or cooling operation

AIRSTAGE J-III L

8HP - 12HP 3 Models
• 3 phase

Page 48~



Heat Pump type
for heating or cooling operation

AIRSTAGE J-III

4HP - 6HP 3 models
• Single phase

Page 52~



Heat Pump type
for heating or cooling operation

AIRSTAGE J-IIS

4HP - 6HP 3 models
• Single phase

Page 56~

CONTENTS

Flexible Solutions	4
AIRSTAGE™ New Product Lineup	6
Light Commercial Solutions	8
Commercial Solutions	12

AIRSTAGE™ CORE TECHNOLOGY

High Energy Efficiency	18
Maximised Comfort	20
Consistent Reliability	22
Design Flexibility	24
Easy Installation	26
Easy Service & Maintenance	28

AIRSTAGE™ SERIES

AIRSTAGE™ Lineup	32
Heat Recovery Type AIRSTAGE™ VR-II	34
Heat Pump Type AIRSTAGE™ V-III	42
Heat Pump Type AIRSTAGE™ J-III L	48
Heat Pump Type AIRSTAGE™ J-III	52
Heat Pump Type AIRSTAGE™ J-IIS	56

AIRSTAGE™ INDOOR UNITS

Indoor Units Lineup	62
4-way Flow Compact Cassette	64
4-way Flow Cassette	66
Circular Flow Cassette	68
Mini Duct	70
Slim Duct / Slim Concealed Floor	72
Medium Static Pressure Duct	74
High Static Pressure Duct	76
Compact Floor	78
Floor / Ceiling	80
Ceiling	82
Wall Mounted (EEV Internal / External)	84

AIRSTAGE™ CONTROL SYSTEMS

Optimised Control Solutions	92
Control System Overview	94
Comparison Table of Controllers	96
• Individual Controller	98
• Centralised Controller	104
• Convertor / Adaptor	114

VENTILATION

Energy Recovery Ventilator	124
Outdoor Air Unit	126

AIRSTAGE™ OPTION

Auto Louver Grille Kit	129
Optional Parts List	130
Optional Parts	132

ABOUT US

Our History	140
Global Network	142
High Quality Development & Production Facilities	144
Case Studies	146

SUPPORT

AIRSTAGE™ Support	150
AIRSTAGE™ / Rac Support Tool	152
Quick Service & Maintenance	154
Service Tool	156
Web Monitoring Tool	157

FLEXIBLE SOLUTIONS

Fujitsu General have been developing and manufacturing high quality and energy efficient products for more than 35 years. Using the latest Japanese technology and state of the art expertise, our products have been designed in accordance with our aim of creating the most comfortable environment possible, regardless of the project type or design.

AIRSTAGE™ Series



Property Suitability



RESIDENTIAL & LIGHT COMMERCIAL

Fujitsu General offer a diverse range of air conditioning systems focused on residential and small sized buildings.



COMMERCIAL


Fujitsu General provide single and modular type VRF systems with efficient operation, comfort, design flexibility, easy installation and consistent reliability.



AIRSTAGE™ NEW PRODUCT LINEUP

VRF AIRSTAGE™ J-III L

- 8HP to 12HP class - 3 phase 3 models
- Compact and noise reducing design
- Flexible installation
- Up to 22 connectable indoor units



AIRSTAGE™ J-III L

VRF AIRSTAGE™ VR-II / V-III

- Expanded outdoor unit lineup with new 16HP model
- Up to 48HP capacity across 33 models
- Up to 64 connectable indoor units
- Greater design flexibility



AIRSTAGE™ VR-II
AIRSTAGE™ V-III

Remote Controllers

Wired Remote Controller (Touch Panel)

- Easy-to-use with a simple user-friendly interface
- 2 separate set points for heating and cooling
- Automatically changes mode between heating or cooling
- Controls up to 16 indoor units



Simple Remote Controller

- Controls up to 16 indoor units
- Simple and stylish design
- Large LCD screen
- Provides access to basic operation functions



Without
Operation
Mode

Centralised Control

Touch Panel Controller (with web control)

- Controls up to 400 indoor units
- Control and monitor via LAN or internet
- Easy maintenance and installation
- Central control and monitoring of small to medium sized buildings



System Controller Software

Small to large scale buildings

- Up to a maximum of 4 VRF network systems, 1600 indoor units, and 400 outdoor units can be controlled
- Simple BMS, 3rd party devices supported by Modbus communication can be controlled

System Controller Lite Software

Small to medium scale buildings

- Up to a maximum of 1 VRF network system, 400 indoor units, and 100 outdoor units can be controlled



Converter / Adaptor

Options

- A range of converters and adaptors, with both software and hardware options

BACnet® Gateway




Software
(1600 units)

KNX® Converter



Hardware
(128 units)



For VRF
(128 units)

Service Maintenance & Monitoring Tools

Service Tool Software

- Evaluate up to 400 indoor units and 100 outdoor units
- Extensive monitoring and analysis functions available

Web Monitoring Tool Software

- Troubleshooting is performed by monitoring each air conditioning unit remotely during periodical system checks
- VRF systems monitor up to 1600 indoor units
- Automatic refrigeration cycle check




SMALL OFFICES

Fujitsu General provide a wide range of solutions designed to meet the needs of a small building. With energy saving features, low noise design and centralised control, this range is sure to meet your light commercial projects requirements.

AIRSTAGE™ J-III L



Energy saving solutions suitable for meeting rooms and private offices

When there are no people in the room, the save energy operation feature can start automatically to prevent unnecessary power consumption by utilising a human sensor feature and external input / output kit.



Compact outdoor unit with low noise

This compact outdoor unit achieves significant space saving, meaning you can install it on a rooftop or in a plant room. This unit secures enough static pressure even if there are louvers. Low noise operation is possible at night by utilising low noise mode.



NEW

Small VRF System

Up to 12HP using the compact outdoor unit

The small VRF system is suitable for buildings with multiple small rooms. Max. 22 indoor units can be connected.

Even airflow throughout your space




The Circular Airflow Cassette creates a consistent and even temperature via multi-directional airflow functionality.



Each louver can be set individually by the controller* to protect people from being exposed to direct airflow.



Energy saving operation commences when there are no occupants by linking up with the human sensor option. The unit will adjust its operation depending on the presence of occupants within a given room. The human sensor detects movement and activates or deactivates energy saving mode accordingly.



Human sensor (option)

Indoor units



Extensive range of low capacity indoor units to suit small rooms or spaces.

NEW

Centralised control of both air conditioning and lighting

It is possible to perform centralised control of the operation of lighting and ventilation equipment in addition to air conditioners. This is useful in allowing whole building energy saving management and control.

System Controller Lite



*Touch panel wired RC (UTY-RNRYZ2), Touch Panel Controller (UTY-DTGYZ1), System Controller (UTY-APGXZ1), System Controller Lite (UTY-ALGXZ1)

SHOPS, RESTAURANTS & MIXED USE DEVELOPMENTS


Purpose built and tenant friendly solutions for small commercial complexes.

COMPLEX BUILDING



Centralised control of air conditioning for all tenants

Centralised control through the simple touch panel enables individual tenant scheduled operation and electricity charge apportionment.*



Remote monitoring

Air conditioning systems can be monitored from a remote location. This means less downtime and faster diagnostics of operational errors.




High Static Pressure Duct

Air conditioning options for open areas

Large duct system suitable or appropriate for high ceiling and large open atrium spaces

AIRSTAGE™ Small VRF system



Circular Flow Cassette



NEW Uniform air distribution for large areas

Air distribution design allows for circular airflow to spread to every corner of the room.



SHOPS



Capable of cooling in low ambient conditions

Low outside air temperature cooling operation is necessary in winter in stores with a lot of heat inside. Our air conditioning systems allow flexibility supporting cooling operation at -15°C.

30-150 Pa



Medium Static Pressure Duct

RESTAURANT

*Option UTY-PTGXA required for ECA

HOTELS & APARTMENTS

Fujitsu General provides energy saving air conditioning systems offering flexible installation and cutting edge design solutions for hotels and apartments that also take into account comfort, efficiency, external appearance, and system safety features.

AIRSTAGE™ VR-II

Individual cooling and heating responsiveness

Heat recovery functionality allows simultaneous cooling and heating operation, with a maximum outdoor capacity of 48HP.



Smart and cutting edge design. Extensive lineup from 8HP to 48HP in 2HP increments. Connectable indoor unit capacity ratio of 50 to 150%

8HP - 48HP 33 models


- Space saving combinations: 8HP to 48HP / 21 models
- Energy efficiency combinations: 16HP to 42HP / 12 models

Large area air conditioning for reception and lobby areas

High Static Pressure Duct suitable for large spaces with high ceilings.




High Static Pressure Duct



Guest room air conditioning delivering excellent comfort, energy efficiency and easy installation

Space saving

Mini duct type with 198mm height and 450mm depth. This can be easily installed in narrow ceiling spaces.



Mini Duct



Comfortable airflow

The Auto Louver Grille Kit achieves comfortable airflow by adjusting the direction of airflow.



Simple Remote Controller with sophisticated design

Room card switch available

Using the room card prevents guests from forgetting to switch off the air conditioner when departing their room.



Use of an external connection switch

Ventilation support

Outdoor Air Units connect with the VRF system to meet ventilation requirements.



Outdoor Air Unit

Centralised control in shared spaces

Air conditioning in shared spaces such as waiting areas and hallways are controlled centrally. Temperature and operating conditions can be managed without manual adjustment by guests.



System Controller



LARGE BUILDINGS

Fujitsu General provides modular VRF systems that are highly efficient, reliable and offer flexible installation for large or high rise buildings.

Diverse lineup suitable to match your operating environment

The VRF V-III series lineup is designed to meet various needs with energy efficient models, these units are compatible with high outdoor air ambient temperatures.



Heat Pump Modular type for heating or cooling operation

AIRSTAGE™ V-III



8HP - 48HP 33 Models

- Space saving combinations: 8HP to 48HP / 21 models
- Energy efficiency combinations: 16HP to 42HP / 12 models

Centralised control of both air conditioning and lighting

It is possible to perform centralised control of the operation of lighting and ventilation equipment in addition to air conditioners. This is useful in allowing whole building energy saving management and control.

System Controller
(UTY-APGXZ1)
System Controller Lite
(UTY-ALGXZ1 & UTY-PLGXX2)




4-way Flow Cassette




Improved airflow distribution

The unique design of the louvers and added space between the chassis and ceiling maximises airflow distribution within the room.




Bottom view



Round louver

High ceiling mode

This cassette can be installed up to a ceiling height of 4.2m (36/45/54).



BMS integration

Major protocols including Modbus, BACnet, KNX and LonWorks are supported allowing Fujitsu AIRSTAGE™ equipment to be easily integrated.





AIRSTAGE™ CORE TECHNOLOGY

- HIGH ENERGY EFFICIENCY
- MAXIMISED COMFORT
- CONSISTENT RELIABILITY
- DESIGN FLEXIBILITY
- EASY INSTALLATION
- EASY SERVICE & MAINTENANCE




AIRSTAGE™

HIGH ENERGY EFFICIENCY

Energy Efficiency Comparison


Operational efficiency has improved significantly through the new DC twin rotary compressor, inverter technology and large heat exchanger.



Performance and Control


Room temperature set point limitation

The minimum and maximum temperature ranges can be limited, which provides further energy saving functionality whilst maintaining the comfort of the occupants.




Auto-off timer

The new wired remote controller is equipped with an OFF timer function that automatically stops the units operation when a fixed time has elapsed from the start of operation. The schedule for the auto off timer can be programmed.




Energy saving management

A variety of energy saving operations can be set and managed depending on the season, weather and time period using the system controller.



Operational capacity

Operation capacity can be set in 5 simple steps for rated capability. The power consumption at peak is cut down and the maximum load is suppressed.




MAXIMISED COMFORT



Precise refrigerant flow control

Precise and smooth refrigerant flow control is achieved by using the DC Inverter control in conjunction with an individual indoor unit electronic expansion valve. This allows the set temperature to be controlled $\pm 0.5^\circ\text{C}$.




Quiet operation


Low noise mode

Two low noise modes can be selected automatically through the 'quiet priority setting' and 'capacity priority setting' depending on the noise or capacity requirements. This feature can be controlled via an outdoor unit external input and/or system controller.

Quiet priority setting





Capacity priority setting




Auto change over function

When the auto setting is selected, the unit automatically switches between cooling and heating modes according to the set temperature and room temperature.




The auto change over setting allows for the product to easily switch between the cooling and heating modes regardless of the operation mode of the other indoor units. This can be done via a specific indoor unit with wired remote controller. This ensures comfortable operation all year round.



Non-stop oil recovery operation

A comfortable room temperature is maintained during the oil recovery mode as the unit continues to operate without stopping the cooling or heating operation.

*Not available on the AIRSTAGE VR-II




CONSISTENT RELIABILITY



Outdoor unit rotational operation

The compressor starting order is rotated so that the running time is shared.




Note: Rotational operation is alternated by the start / stop timing of the compressor.

Backup operation


If one compressor fails, backup operation will be performed by the remaining compressors*.

* Note: Backup operation may not be possible depending on the system error.




Advanced refrigerant control

Innovative compressor control logic has been introduced in order to balance the refrigerant mass flow rate of each outdoor unit by controlling the inverter speed.




Liquid flow back protection

Through a larger accumulator, the non vapourised refrigerant stays within the accumulator to ensure no liquid refrigerant is being fed into the compressor.



Adoption of blue fin heat exchanger

The corrosion resistance of the outdoor heat exchanger has been improved by the introduction of blue fin treatment.



DESIGN FLEXIBILITY


Overall piping length 1,000m




High static pressure

The outdoor unit can have a condenser hood easily connected with a static pressure up to 82Pa. This allows outdoor units to be installed within plant rooms in high rise buildings.


Powerful discharge of air prevents a short-circuit.



Previous model



VR-II, V-III



Large diameter fan and DC motor has been utilised allowing an external static pressure of up to 82Pa. This is approximately 2.6 times greater than the previous model.


80 Pa (VR-II)
82 Pa (V-III)

High capacity connection

<p>AIRSTAGE™ VR-II series Heat Recovery type</p> <p>Connectable indoor unit capacity range 50% to 150%</p> <p>Connectable indoor unit number up to 64</p>	<p>AIRSTAGE™ V-III series Heat Pump type</p> <p>Connectable indoor unit capacity range 50% to 150%</p> <p>Connectable indoor unit number up to 64</p>	
<p>AIRSTAGE™ J-III series Heat Pump type</p> <p>Connectable indoor unit capacity range 50% to 150%</p> <p>Connectable indoor unit number up to 22</p>	<p>AIRSTAGE™ J-III series Heat Pump type</p> <p>Connectable indoor unit capacity range 50% to 150%</p> <p>Connectable indoor unit number up to 10</p>	<p>AIRSTAGE™ J-IIS series Heat Pump type</p> <p>Connectable indoor unit capacity range 50% to 130%</p> <p>Connectable indoor unit number up to 8</p>


Wide operating range

Installation in extreme temperature conditions is possible due to an increase in operational range.



*2. Note: When a modular outdoor unit connection is used, operating range is from -5°C to 46°C in cooling.


EASY INSTALLATION



Easily transported

Easily craned using lifting belt hooks

Design of outdoor unit allows for lifting straps to be used.



Transporting by forklift

Transport with forklift is possible.




Can be transported in a small elevator




Easy access

By adopting a L-Shape front panel that can be removed, the work space for installation and service has been significantly improved by this new design.




Flexible piping connection

Piping and wiring are available to the front, rear, bottom and side.




Simple wiring work

Installation of the wiring systems is made easier as the communication wiring can be installed in a series configuration between the indoor, outdoor and RB units.




Easy evacuation using vacuum mode function

The vacuum mode function enables all expansion valves of the indoor units to be fully opened, making it easy to evacuate all the air inside pipe lines and indoor units.



Automatic address setting

The address of the indoor unit, RB unit and signal amplifier can be set through the automatic function setting on the outdoor unit PCB.



Easy commissioning using the Service Tool

The service tool can be used to check system characteristics including the refrigerant temperature, pressure and the operating status of the electronic expansion valves, making it easy to determine whether the units are functioning correctly.



EASY SERVICE & MAINTENANCE




Easy maintenance design

Self diagnosis can be performed using the LED display which makes it easy to check function setting status, refrigerant temperature, pressure, compressor operation time and other factors.



Easy to read 7 segment LED: Provides detailed operational and error status without using any specific equipment.



7 segment LED

- Operation mode status
- Discharge temperature/Pressure status
- Compressor operation indication
- Address/type/number of outdoor unit

Movable PCB panel
Easier for maintenance work behind the PCB



Error status can be checked easily via the indoor unit wired controller

An error code is displayed on a liquid crystal screen.

Wired Remote Controller

Simple Remote Controller

Wired Remote Controller (Touch panel)

No.	Date	Time	Address	Code
1	2012/ 8/ 1	11:00AM	002-01	141
2	2012/ 7/30	2:53AM	002-02	143
3	2012/ 7/28	10:55AM	002-02	142
4	2012/ 7/23	11:00AM	002-01	141
5	2012/ 7/22	11:00AM	002-01	141
6	2012/ 7/21	11:00AM	002-01	141

Error status can be checked easily by outdoor unit display


Error information

Error code

Abnormal indoor unit address

Error diagnosis using the Service Tool


- Detailed operation status and recent error history can be checked and analysed by using the Service Tool




Remote monitoring

The Web Monitoring system allows you to view system operation anytime over the internet in real time.

Monitoring Side



VRF Network System Side





AIRSTAGE
INVERTER

AIRSTAGE™ SERIES

The 5 series of the AIRSTAGE™ range has a total of 73 outdoor models to meet the project scope or building size requirements

The AIRSTAGE™ series outdoor units have been developed with structural designs and advanced inverter technology to provide higher efficiency. High durability technology has also been incorporated to ensure long-term use.

AIRSTAGE™ LINEUP

HEAT RECOVERY TYPE AIRSTAGE™ VR-II

HEAT PUMP TYPE AIRSTAGE™ V-III

HEAT PUMP TYPE AIRSTAGE™ J-III L

HEAT PUMP TYPE AIRSTAGE™ J-III

HEAT PUMP TYPE AIRSTAGE™ J-IIS



AIRSTAGE™

AIRSTAGE™ LINEUP

Fujitsu General's range of AIRSTAGE™ products allow installation flexibility to meet the unique size and application needs of your project.



Outdoor units range

HP	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
kW class	12.1	14.0	15.5	22.4	28.0	33.5	40.0	45.0	50.4	55.9	61.5	67.0	73.5	78.5	85.0	90.0	95.0	100.5	107.0	112.0	118.5	123.0	128.0	135.0	
NEW AIRSTAGE VR-II Heat Recovery	Space Saving																								
	High Efficiency																								
NEW AIRSTAGE V-III Heat Pump	Space Saving																								
	High Efficiency																								



NEW AIRSTAGE J-III L Heat Pump	Space Saving																								
AIRSTAGE J-III Heat Pump	High Efficiency																								
AIRSTAGE J-III S Heat Pump	Space Saving																								

HEAT RECOVERY TYPE

AIRSTAGE™ VR-II series

- Smart and cutting edge design
- Extensive lineup from 8HP to 48HP in 2HP increments
- Connectable indoor unit capacity ratio of up to 150%

System Outline

Simultaneous cooling and heating operation using one refrigerant system

Cooling and heating can be freely selected for each indoor unit to provide simultaneous cooling and heating in rooms with large temperature differences.


Annual cooling operation

The VR-II series provide annual cooling operation functionality for spaces that require constant temperature control throughout the year.

Temperature difference control


The operation mode can be freely changed when there are large temperature differences during the day, such as between seasons.

Large Building



Our heat recovery systems can achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.



Our heat recovery systems can achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.



Features

Efficiency during operation

A high COP is achieved for all combinations through our unique heat exchanger structure, high efficient DC twin compressor and our own proprietary technologies.



***For 24 HP Combination**

Space saving → Energy efficiency

COP 15% UP

Energy saving technology that enhances operational efficiency



Powerful large propeller fan

By using CFD*1 technology, the newly designed fan achieves high performance and low noise operation.

*1. CFD = Computational Fluid Dynamics



3 phase DC fan motor

Efficiency is improved with the high efficient motor with sophisticated drive control. Additionally the DC fan motor exhibits a low noise output.



Subcool heat exchanger

High heat exchanger efficiency is achieved by using an internal projection shape with double pipe construction.



Sine-wave DC inverter control

High efficiency is realised by adoption of reduced switching loss IPM.




Large capacity DC inverter compressor

The large capacity high efficient DC twin rotary compressor with excellent part load capability.




4-face heat exchanger

Heat exchanger efficiency is significantly improved by the introduction of a new 4-face heat exchanger that increases the effective surface area.



Front intake port (corner cut air intake structure)

In multiple outdoor unit installations, the unique front intake design improves airflow into the Heat Exchanger.





All inverter compressor


Large capacity DC inverter compressor

Large capacity high efficient DC twin rotary compressor with excellent intermediate capability.




High efficiency compressor speed control

Comfortable space with small room temperature changes and little energy loss is created by 0.1Hz steps for compressor speed control.




Multiple outdoor operation control

When multiple outdoor units are connected, a sophisticated operation is performed by each compressor. Rather than running one compressor at full load and distributing refrigerant to one heat exchanger, this control method operates all compressors at part load and distributes refrigerant to all of the heat exchangers allowing for overall system efficiency to be improved.




Heat exchanger refrigerant control

The heat exchanger in the outdoor unit is split into two parts (top and bottom). The efficiency of the heat exchanger has been improved by adopting an optimum refrigerant path control where the refrigerant is distributed more into the top heat exchanger as this is where there is a greater air flow intake.



Flexible piping connection


Flexible refrigerant pipe work is possible through the use of various piping and RB Unit connections to match the floor layout and building structure.




Flexible installation of RB unit




- Compact and slim design saves space
- A drain pipe is not required
- The control box position can be changed to meet the installation conditions




- Compact space saving design
- A drain pipe is not required
- Simple installation series connection design



Easy maintenance in narrow spaces



- Maintenance can be performed from the side
- Sliding down the panel on the electric box allows for easy repair and maintenance



Outdoor units lineup

• Combinations other than those specified are not supported.

Space saving combinations

22.4kW (8HP) AJTA72GALH UNIT: AJTA72GALH	28.0kW (10HP) AJTA90GALH UNIT: AJTA90GALH	33.5kW (12HP) AJT108GALH UNIT: AJT108GALH	40.0kW (14HP) AJT126GALH UNIT: AJT126GALH	45.0kW (16HP) AJT144GBLH UNIT: AJT144GBLH
50.4kW (18HP) AJT162GALH UNIT: AJTA90/A72GALH	56.0W (20HP) AJT180GALH UNIT: AJTA90/A90GALH	61.5kW (22HP) AJT198GALH UNIT: AJT108/A90GALH	67.4kW (24HP) AJT216GBLH UNIT: AJT144GBLH/A72GALH	73.0kW (26HP) AJT234GBLH UNIT: AJT144GBLH/A90GALH
78.5kW (28HP) AJT252GBLH UNIT: AJT144GBLH/108GALH	85.0kW (30HP) AJT270GBLH UNIT: AJT144GBLH/126GALH	90.0kW (32HP) AJT288GBLH UNIT: AJT144/144GBLH	95.4kW (34HP) AJT306GBLH UNIT: AJT144GBLH/A90/A72GALH	101.0kW (36HP) AJT324GBLH UNIT: AJT144GBLH/A90/A90GALH
106.5kW (38HP) AJT342GBLH UNIT: AJT144GBLH/108/A90GALH	112.4kW (40HP) AJT360GBLH UNIT: AJT144/144GBLH/A72GALH	118.0kW (42HP) AJT378GBLH UNIT: AJT144/144GBLH/A90GALH	123.5kW (44HP) AJT396GBLH UNIT: AJT144/144GBLH/108GALH	130.0kW (46HP) AJT414GBLH UNIT: AJT144/144GBLH/126GALH
135.0kW (48HP) AJT432GBLH UNIT: AJT144/144/144GBLH				


Energy efficiency combinations

44.8kW (16HP) AJT144GALH UNIT: AJTA72/A72GALH	55.9kW (20HP) AJT180GALHH UNIT: AJT108/A72GALH	67.2kW (24HP) AJT216GALHH UNIT: AJTA72/A72/A72GALH	72.8kW (26HP) AJT234GALHH UNIT: AJTA90/A72/A72GALH	78.3kW (28HP) AJT252GALHH UNIT: AJT108/A72/A72GALH
83.9kW (30HP) AJT270GALHH UNIT: AJT108/A90/A72GALH	89.4kW (32HP) AJT288GALHH UNIT: AJT108/108/A72GALH	95.0kW (34HP) AJT306GALHH UNIT: AJT108/108/A90GALH	100.5kW (36HP) AJT324GALHH UNIT: AJT108/108/108GALH	107.0kW (38HP) AJT342GALHH UNIT: AJT126/108/108GALH
112.0kW (40HP) AJT360GBLHH UNIT: AJT144GBLH/108/108GALH	118.5kW (42HP) AJT378GBLHH UNIT: AJT144GBLH/126/108GALH			

Dimensions



8 / 10HP: AJTA72GALH / AJTA90GALH

(Unit: mm)



12 / 14 / 16HP: AJT108GALH / AJT126GALH / AJT144GBLH

(Unit: mm)



Space saving combinations

Rating capacity range		HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48		
Model name			AJTA72GALH	AJTA90GALH	AJT108GALH	AJT126GALH	AJT144GBLH	AJT162GALH	AJT180GALH	AJT198GALH	AJT216GBLH	AJT234GBLH	AJT252GBLH	AJT270GBLH	AJT288GBLH	AJT306GBLH	AJT324GBLH	AJT342GBLH	AJT360GBLH	AJT378GBLH	AJT396GBLH	AJT414GBLH	AJT432GBLH		
Unit 1			AJTA72GALH	AJTA90GALH	AJT108GALH	AJT126GALH	AJT144GBLH	AJT162GALH	AJT180GALH	AJT198GALH	AJT216GBLH	AJT234GBLH	AJT252GBLH	AJT270GBLH	AJT288GBLH	AJT306GBLH	AJT324GBLH	AJT342GBLH	AJT360GBLH	AJT378GBLH	AJT396GBLH	AJT414GBLH	AJT432GBLH		
Unit 2			AJTA72GALH	AJTA90GALH	AJT108GALH	AJT126GALH	AJT144GBLH	AJT162GALH	AJT180GALH	AJT198GALH	AJT216GBLH	AJT234GBLH	AJT252GBLH	AJT270GBLH	AJT288GBLH	AJT306GBLH	AJT324GBLH	AJT342GBLH	AJT360GBLH	AJT378GBLH	AJT396GBLH	AJT414GBLH	AJT432GBLH		
Unit 3			AJTA72GALH	AJTA90GALH	AJT108GALH	AJT126GALH	AJT144GBLH	AJT162GALH	AJT180GALH	AJT198GALH	AJT216GBLH	AJT234GBLH	AJT252GBLH	AJT270GBLH	AJT288GBLH	AJT306GBLH	AJT324GBLH	AJT342GBLH	AJT360GBLH	AJT378GBLH	AJT396GBLH	AJT414GBLH	AJT432GBLH		
Maximum connectable indoor unit*1			15	16	17	21	24	27	30	32	36	39	42	45	48	51	54	57	60	63	64	64	64		
Indoor unit connectable capacity		Cooling	kW		11.2 to 33.6	14.0 to 42.0	16.8 to 50.2	20.0 to 60.0	22.5 to 67.5	25.2 to 75.6	28.0 to 84.0	30.8 to 92.2	33.7 to 101.1	36.5 to 109.5	39.3 to 117.7	42.5 to 127.5	45.0 to 135.0	47.7 to 143.1	50.5 to 151.5	53.3 to 159.7	56.2 to 168.6	59.0 to 177.0	61.8 to 185.2	65.0 to 195.0	67.5 to 202.5
Power source		3-phase 4 wire, 400 V, 50Hz											3-phase 4 wire, 400 V, 50Hz												
Capacity		Cooling	kW		22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.4	73.0	78.5	85.0	90.0	95.4	101.0	106.5	112.4	118.0	123.5	130.0	135.0
		Heating	kW		25.0	31.5	37.5	45.0	48.5	56.5	63.0	69.0	73.5	80.0	86.0	93.5	97.0	105.0	111.5	117.5	122.0	128.5	134.5	142.0	145.5
Input power		Cooling	kW		6.14	8.37	10.04	13.00	14.48	14.51	16.74	18.41	20.62	22.85	24.52	27.48	28.96	28.99	31.22	32.89	35.10	37.33	39.00	41.96	43.44
		Heating	kW		6.01	8.41	9.57	12.31	14.06	14.42	16.82	17.98	20.07	22.47	23.63	26.37	28.12	28.48	30.88	32.04	34.13	36.53	37.69	40.43	42.18
EER		Cooling	W/W		3.65	3.35	3.34	3.08	3.11	3.47	3.35	3.34	3.27	3.19	3.20	3.09	3.11	3.29	3.24	3.24	3.20	3.16	3.17	3.10	3.11
COP		Heating	W/W		4.16	3.75	3.92	3.66	3.45	3.92	3.75	3.84	3.66	3.56	3.64	3.55	3.45	3.69	3.61	3.67	3.57	3.52	3.57	3.51	3.45
Air flow rate		High	m ³ /h (l/s)		11,100 (3,084)	11,100 (3,084)	13,000 (3,611)	13,000 (3,611)	13,000 (3,611)	11,100*2 (3,084*2)	11,100*2 (3,084*2)	13,000+11,100 (3,611+3,084)	13,000+11,100 (3,611+3,084)	13,000*2 (3,611*2)	13,000*2 (3,611*2)	13,000*2 (3,611*2)	13,000*2 (3,611*2)	13,000+11,100*2 (3,611+3,084*2)	13,000+11,100*2 (3,611+3,084*2)	13,000*2+11,100 (3,611*2+3,084)	13,000*2+11,100 (3,611*2+3,084)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	
Sound pressure level*2 / Power level		Cooling	dB (A)		56	58	57	61	61	60	61	61	62	63	62	64	64	64	64	65	65	65	66	66	
		Heating	dB (A)		58	59	59	61	64	62	62	62	65	65	66	67	66	66	66	68	68	68	68	69	
Maximum external static pressure			Pa		80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	
Compressor motor output			kW		7.5	7.5	11.0	11.0	11.0	7.5*2	7.5*2	11.0*7.5	11.0*7.5	11.0*7.5	11.0*2	11.0*2	11.0*2	11.0*2	11.0*7.5*2	11.0*7.5*2	11.0*2+7.5	11.0*2+7.5	11.0*3	11.0*3	
Heat exchanger fin			Blue fin		Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin						
Dimensions		Height	mm		1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
		Width	mm		930	930	1,240	1,240	1,240	930*2	930*2	1,240+930	1,240+930	1,240+930	1,240*2	1,240*2	1,240*2	1,240+930*2	1,240+930*2	1,240*2+930	1,240*2+930	1,240+930	1,240*3	1,240*3	
		Depth	mm		765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	
Weight			kg		262	262	286	286	286	262*2	262*2	286+262	286+262	286+262	286*2	286*2	286*2	286+262*2	286+262*2	286*2+262	286*2+262	286*3	286*3	286*3	
Refrigerant		Type	R410A		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A		
		Charge	kg		11.8	11.8	11.8	11.8	11.8	11.8*2	11.8*2	11.8*2	11.8*2	11.8*2	11.8*2	11.8*2	11.8*3	11.8*3	11.8*3	11.8*3	11.8*3	11.8*3	11.8*3		
Connection pipe diameter		Liquid	mm		12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05		
		Discharge Gas	mm		15.88	19.05	19.05	22.22	22.22	22.22	22.22	28.58	28.58	28.58	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92		
		Suction Gas	mm		22.22	22.22	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27		
Operation range		Cooling	°C		-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46							
		Heating	°C		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21							
		Cooling/Heating	°C		-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21							

Energy efficiency combinations

Rating capacity range		HP	16	22	24	26	28	30	32	34	36	38	40	42		
Model name			AJT144GALH	AJT180GALH	AJT216GALH	AJT234GALH	AJT252GALH	AJT270GALH	AJT288GALH	AJT306GALH	AJT324GALH	AJT342GALH	AJT360GBLH	AJT378GBLH		
Unit 1			AJTA72GALH	AJT108GALH	AJTA72GALH	AJTA90GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT126GALH	AJT144GBLH	AJT144GBLH		
Unit 2			AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA90GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT108GALH	AJT126GALH		
Unit 3			AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA72GALH	AJTA90GALH	AJT108GALH	AJT108GALH	AJT108GALH			
Maximum connectable indoor unit*1			24	29	36	39	41	44	47	50	53	57	60	63		
Indoor unit connectable capacity		Cooling	kW		22.4 to 67.2	28.0 to 83.8	33.6 to 100.8	36.4 to 109.2	39.2 to 117.4	42.0 to 125.8	44.7 to 134.1	47.5 to 142.5	50.3 to 150.7	53.5 to 160.5	56.0 to 168.0	59.3 to 177.7
Power source		3-phase 4 wire, 400 V, 50Hz														
Capacity		Cooling	kW		44.8	55.9	67.2	72.8	78.3	83.9	89.4	95.0	100.5	107.0	112.0	118.5
		Heating	kW		50.0	62.5	75.0	81.5	87.5	94.0	100.0	106.5	112.5	120.0	123.5	131.0
Input power		Cooling	kW		12.28	16.18	18.42	20.65	22.32	24.55	26.22	28.45	30.12	33.08	34.56	37.52
		Heating	kW		12.02	15.58	18.03	20.43	21.59	23.99	25.15	27.55	28.71	31.45	33.20	35.94
EER		Cooling	W/W		3.65	3.45	3.65	3.53	3.51	3.42	3.41	3.34	3.34	3.23	3.24	3.16
COP		Heating	W/W		4.16	4.01	4.16	3.99	4.05	3.92	3.98	3.87	3.92	3.82	3.72	3.64
Air flow rate		High	m ³ /h (l/s)		11,100*2 (3,084*2)	13,000+11,100 (3,611+3,084)	11,100*3 (3,084*3)	11,100*3 (3,084*3)	13,000+11,100*2 (3,611+3,084*2)	13,000+11,100*2 (3,611+3,084*2)	13,000*2+11,100 (3,611*2+3,084)	13,000*2+11,100 (3,611*2+3,084)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	
Sound pressure level*2 / Power level		Cooling	dB (A)		59	60	61	62	61	62	61	62	62	64	64	65
		Heating	dB (A)		61	62	63	63	63	63	64	64	64	65	66	67
Maximum external static pressure			Pa		80	80	80	80	80	80	80	80	80	80	80	80
Compressor motor output			kW		7.5*2	11.0*7.5	7.5*3	7.5*3	11.0*7.5*2	11.0*7.5*2	11.0*7.5	11.0*7.5	11.0*3	11.0*3	11.0*3	
Heat exchanger fin			Blue fin		Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Dimensions		Height	mm		1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
		Width	mm		930*2	1,240+930	930*3	930*3	1,240+930*2	1,240+930*2	1,240+930*2	1,240+930*2	1,240*3	1,240*3	1,240*3	
		Depth	mm		765	765	765	765	765	765	765	765	765	765		
Weight			kg		262*2	286+262	262*3	262*3	286+262*2	286+262*2	286+262	286+262	286*3	286*3	286*3	
Refrigerant		Type	R410A													

HEAT PUMP TYPE

NEW AIRSTAGE™ V-III series

- Smart and cutting edge design
- Extensive lineup from 8HP to 48HP in 2HP increments
- Connectable indoor unit capacity ratio of up to 150%

System Outline

Excellent energy saving


Our heat pump inverter type systems achieve energy efficient operation for both cooling or heating operation with the use of inverter technology.

High design flexibility for various building requirements

High rise building air conditioning design and installation flexibility is achieved with concentrated roof top or individual plant area installation made possible by flexible piping options and the high static pressure design.


Easy installation and maintenance

The flexible communication wiring method and piping connections makes installation and maintenance easy.



System configuration example



- This system is used for medium and large sized buildings. Connecting a combination of outdoor units makes it possible to create a high-capacity system.
- This example shows the connection of multiple indoor units using separation tubes and headers.



Features

Efficiency during operation

A high COP is realised for all combinations by our unique heat exchanger structure, high efficient DC twin compressor along with additional proprietary technologies.



Energy saving technology that enhances operational efficiency



Powerful large propeller fan

By using CFD*1 technology, the newly designed fan achieves high performance and low noise operation. *1. CFD = Computational Fluid Dynamics



3 phase DC fan motor

Efficiency is improved with the high efficient motor with sophisticated drive control. Additionally the DC fan motor exhibits a low noise output.



Subcool heat exchanger

High heat exchanger efficiency is achieved by using an internal projection shape with double pipe construction.




Sine-wave DC inverter control

High efficiency is realised by adoption of reduced switching loss IPM.



Large capacity ALL DC inverter compressor


The large capacity high efficient DC twin rotary compressor with 0.1Hz steps compressor speed control



4-face heat exchanger

Heat exchanger efficiency is significantly improved by the introduction of a new 4-face heat exchanger that increases the effective surface area.


Front intake port (corner cut air intake structure)



Advanced energy saving control


Multiple outdoor operation control

This control method operates all compressors at part load and distributes refrigerant to all heat exchangers to improve the overall system efficiency.



Heat exchanger refrigerant control

The efficiency of the top and bottom heat exchanger in the outdoor unit has been improved by adopting an optimum refrigerant path control.



Outdoor units lineup

• Combinations other than those specified are not supported.

Space saving combinations

22.4kW (8HP) AJY072LALBH UNIT: AJY072LALBH	28.0kW (10HP) AJY090LALBH UNIT: AJY090LALBH	33.5kW (12HP) AJY108LALBH UNIT: AJY108LALBH	40.0kW (14HP) AJY126LALBH UNIT: AJY126LALBH	45.0kW (16HP) AJY144LALBH UNIT: AJY144LALBH
50.4kW (18HP) AJY162LALBH UNIT: AJY090/072LALBH	56.0W (20HP) AJY180LALBH UNIT: AJY090/090LALBH	62.4kW (22HP) AJY198LALBH UNIT: AJY126/072LALBH	68.0kW (24HP) AJY216LALBH UNIT: AJY126/090LALBH	73.0kW (26HP) AJY234LALBH UNIT: AJY144/090LALBH
80.0kW (28HP) AJY252LALBH UNIT: AJY126/126LALBH	85.0kW (30HP) AJY270LALBH UNIT: AJY144/126LALBH	90.0kW (32HP) AJY288LALBH UNIT: AJY144/144LALBH	96.0kW (34HP) AJY306LALBH UNIT: AJY126/090/090LALBH	101.0kW (36HP) AJY324LALBH UNIT: AJY144/090/090LALBH
108.0kW (38HP) AJY342LALBH UNIT: AJY126/126/090LALBH	113.0kW (40HP) AJY360LALBH UNIT: AJY144/126/090LALBH	118.0kW (42HP) AJY378LALBH UNIT: AJY144/144/090LALBH	125.0kW (44HP) AJY396LALBH UNIT: AJY144/126/126LALBH	130.0kW (46HP) AJY414LALBH UNIT: AJY144/144/126LALBH
135.0kW (48HP) AJY432LALBH UNIT: AJY144/144/144LALBH				


Energy efficiency combinations

44.8kW (16HP) AJY144LALBHH UNIT: AJY072/072LALBH	55.9kW (20HP) AJY180LALBHH UNIT: AJY108/072LALBH	67.2kW (24HP) AJY216LALBHH UNIT: AJY072/072/072LALBH	72.8kW (26HP) AJY234LALBHH UNIT: AJY090/072/072LALBH	78.3kW (28HP) AJY252LALBHH UNIT: AJY108/072/072LALBH
84.8kW (30HP) AJY270LALBHH UNIT: AJY126/072/072LALBH	89.4kW (32HP) AJY288LALBHH UNIT: AJY108/108/072LALBH	95.9kW (34HP) AJY306LALBHH UNIT: AJY126/108/072LALBH	100.5kW (36HP) AJY324LALBHH UNIT: AJY108/108/108LALBH	107.0kW (38HP) AJY342LALBHH UNIT: AJY126/108/108LALBH
113.5kW (40HP) AJY360LALBHH UNIT: AJY126/126/108LALBH	112.0kW (42HP) AJY378LALBHH UNIT: AJY126/126/126LALBH			

Dimensions



8 / 10HP: AJY072LALBH / AJY090LALBH

(Unit: mm)



12 / 14 / 16HP: AJY108LALBH / AJY126LALBH / AJY144LALBH

(Unit: mm)



Space saving combinations

Rating capacity range		HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
Model name			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	
Unit 1			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	
Unit 2			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	
Unit 3			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	
Maximum connectable indoor unit*1			15	16	17	21	24	27	30	33	36	39	42	45	48	51	54	57	60	63	64	64	64	
Indoor unit connectable capacity		Cooling	11.2 to 33.6	14.0 to 42.0	16.8 to 50.2	20.0 to 60.0	22.5 to 67.5	25.2 to 75.6	28.0 to 84.0	31.2 to 93.6	34.0 to 102.0	36.5 to 109.5	40.0 to 120.0	42.5 to 127.5	45.0 to 135.0	48.0 to 144.0	50.5 to 151.5	54.0 to 162.0	56.5 to 169.5	59.0 to 177.0	62.5 to 187.5	65.0 to 195.0	67.5 to 202.5	
Power source			3-phase 4 wire, 400 V, 50Hz										3-phase 4 wire, 400 V, 50Hz											
Capacity		Cooling	22.4	28.0	33.5	40.0	45.0	50.4	56.0	62.4	68.0	73.0	80.0	85.0	90.0	96.0	101.0	108.0	113.0	118.0	125.0	130.0	135.0	
		Heating	25.0	31.5	37.5	45.0	48.5	56.5	63.0	70.0	76.5	81.5	90.0	95.0	100.0	108.0	113.0	121.5	126.5	131.5	140.0	145.0	150.0	
Input power		Cooling	5.20	7.28	8.96	10.96	14.48	12.48	14.56	16.16	18.24	20.29	21.92	23.97	26.02	25.52	27.57	29.20	31.25	33.30	34.93	36.98	39.03	
		Heating	5.17	7.25	8.65	11.17	14.06	12.42	14.50	16.34	18.42	20.88	22.34	24.80	27.26	25.67	28.13	29.59	32.05	34.51	35.97	38.43	40.89	
EER		Cooling	4.31	3.85	3.74	3.65	3.11	4.04	3.85	3.86	3.73	3.60	3.65	3.55	3.46	3.76	3.66	3.70	3.62	3.54	3.58	3.52	3.46	
COP		Heating	4.84	4.35	4.34	4.03	3.45	4.55	4.34	4.28	4.15	3.90	4.03	3.83	3.67	4.21	4.02	4.11	3.95	3.81	3.89	3.77	3.67	
Air flow rate		High	m ³ /h (l/s)	11,100 (3,084)	11,100 (3,084)	13,000 (3,611)	13,000 (3,611)	13,700 (3,806)	11,100*2 (3,084*2)	11,100*2 (3,084*2)	13,000+11,100 (3,611+3,084)	13,000+11,100 (3,611+3,084)	13,700+13,000 (3,806+3,084)	13,000*2 (3,611*2)	13,700+13,000 (3,806+3,611)	13,700*2 (3,806*2)	13,000+11,100*2 (3,611+3,084*2)	13,700+11,100*2 (3,611+3,084*2)	13,000*2+11,100 (3,806+3,084)	13,700+11,100 (3,806+3,084)	13,000*2+11,100 (3,806+3,084)	13,700+11,100 (3,806+3,084)	13,000*2+11,100 (3,806+3,084)	13,700+11,100 (3,806+3,084)
Sound pressure level*2 / Power level		Cooling	56	58	57	60	62	60	61	61	62	63	63	64	65	64	65	64	65	66	66	66	67	
		Heating	58	59	60	62	64	62	62	63	64	65	65	66	67	65	66	66	66	67	68	68	69	
Maximum external static pressure		Pa	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	
Compressor motor output		kW	7.5	7.5	11.0	11.0	11.0	7.5*2	7.5*2	11.0*7.5	11.0*7.5	11.0*7.5	11.0*2	11.0*2	11.0*2	11.0*2	11.0*7.5*2	11.0*7.5*2	11.0*2+7.5	11.0*2+7.5	11.0*2+7.5	11.0*3	11.0*3	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Dimensions		Height	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
		Width	930	930	1,240	1,240	1,240	930*2	930*2	1,240+930	1,240+930	1,240+930	1,240*2	1,240*2	1,240*2	1,240+930*2	1,240+930*2	1,240+930	1,240+930	1,240+930	1,240+930	1,240*3	1,240*3	
		Depth	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	
Weight		kg	252	252	275	275	275	252*2	252*2	275+252	275+252	275*2	275*2	275*2	275*2	275+252*2	275+252*2	275*2+252	275*2+252	275*2+252	275*3	275*3	275*3	
Refrigerant		Type	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
		Charge	11.7	11.7	11.8	11.8	11.8	11.7*2	11.7*2	11.8+11.7	11.8+11.7	11.8*2	11.8*2	11.8*2	11.8*2	11.8+11.7*2	11.8+11.7*2	11.8*2+11.7	11.8*2+11.7	11.8*2+11.7	11.8*3	11.8*3	11.8*3	
Connection pipe diameter		Liquid	12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	
		Suction Gas	22.22	22.22	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27	41.27	
Operation range		Cooling	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	
		Heating	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	

Energy efficiency combinations

Rating capacity range		HP	16	22	24	26	28	30	32	34	36	38	40	42	
Model name			AJY144LALBHH	AJY180LALBHH	AJY216LALBHH	AJY234LALBHH	AJY252LALBHH	AJY270LALBHH	AJY288LALBHH	AJY306LALBHH	AJY324LALBHH	AJY342LALBHH	AJY360LALBHH	AJY378LALBHH	
Unit 1			AJY072LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	
Unit 2			AJY072LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	
Unit 3			AJY072LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	
Maximum connectable indoor unit*1			24	29	36	39	41	45	47	51	53	57	60	64	
Indoor unit connectable capacity		Cooling	22.4 to 67.2	28.0 to 83.8	33.6 to 100.8	36.4 to 109.2	39.2 to 117.4	42.4 to 127.2	44.7 to 134.1	48.0 to 143.8	50.3 to 150.7	53.5 to 160.5	56.8 to 170.2	60.0 to 180.0	
Power source			3-phase 4 wire, 400 V, 50Hz										3-phase 4 wire, 400 V, 50Hz		
Capacity		Cooling	44.8	55.9	67.2	72.8	78.3	84.8	89.4	95.9	100.5	107.0	113.5	120.0	
		Heating	50.0	62.5	75.0	81.5	87.5	95.0	100.0	107.5	112.5	120.0	127.5	135.0	
Input power		Cooling	10.40	14.16	15.60	17.68	19.36	21.36	23.12	25.12	26.88	28.88	30.88	32.88	
		Heating	10.34	13.82	15.51	17.59	18.99	21.51	22.47	24.99	25.95	28.47	30.99	33.51	
EER		Cooling	4.31	3.95	4.31	4.12	4.04	3.97	3.87	3.82	4.12	3.70	3.68	3.65	
COP		Heating	4.84	4.52	4.84	4.63	4.61	4.42	4.45	4.30	4.34	4.21	4.11	4.03	
Air flow rate		High	m ³ /h (l/s)	11,100*2 (3,084*2)	13,000+11,100 (3,611+3,084)	11,100*3 (3,084*3)	11,100*3 (3,084*3)	13,000+11,100*2 (3,611+3,084*2)	13,000+11,100*2 (3,611+3,084*2)	13,000*2+11,100 (3,611*2+3,084)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	13,000*3 (3,611*3)	
Sound pressure level*2 / Power level		Cooling	59	60	61	62	61	63	61	63	64	64	65		
		Heating	61	62	63	63	64	65	64	65	66	66	67		
Maximum external static pressure		Pa	82	82	82	82	82	82	82	82	82	82	82		
Compressor motor output		kW	7.5*2	11.0*7.5	7.5*3	7.5*2	11.0*7.5*2	11.0*7.5*2	11.0*7.5	11.0*7.5	11.0*3	11.0*3	11.0*3		
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin		
Dimensions		Height	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690		
		Width	930*2	1,240+930	930*3	930*3	1,240+930*2	1,240+930*2	1,240+930	1,240+930	1,240*3	1,240*3	1,240*3		
		Depth	765	765	765	765	765	765	765	765	765	765	765		
Weight		kg	252*2	275+252	252*3	252*3	275+252*2	275+252*2	275*2+252	275*2+252	275*3	275*3	275*3		
Refrigerant		Type	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A		
		Charge	11.7*2	11.8+11.7	11.7*3	11.7*3	11.8+11.7*2	11.8+11.7*2	11.8*2+11.7	11.8*2+11.7	11.8*3	11.8*3	11.8*3		
Connection pipe diameter		Liquid	12.70	15.88	15.88	15.88	15.88								

HEAT PUMP TYPE

NEW AIRSTAGE™ J-III L series

Fujitsu General provides air conditioning systems for a wide range of applications from small office buildings and stores to large houses.

System Outline

Compact outdoor unit

The compact design and low noise level enables the units to be installed in various locations with restricted and/or limited spaces such as mechanical rooms and/or rooftops.

Small room application

Up to 22 indoor units can be connected due to the optimum heat exchanger structure. The J-III L series offers flexibility in design, particularly in instances where there are various small rooms present.


Quiet design

Through unit design and innovation we have developed a system that has low noise operation, whilst maintaining a comfortable environment. This potentially allows installation of the units to various places without special sound prevention work.

Small Office

System configuration example


- This system is typically used for small and medium-sized buildings
- This example shows the connection of multiple indoor units using separation tubes and headers



Features

Compact Design

This model is more compact than the conventional 12HP comparable outdoor unit. Discreet installation is available even on the roof top..



Current model

AIRSTAGE™ J-III L

Model / 12HP class

Height difference
1,428mm
▲16%

Space area
0.71m²
▲27%

Advanced high efficiency technology



Ø570mm


Large propeller fan

The high efficiency and the low sound operation is realised by the reduction of draft loss enabled by the Fujitsu General's blade design and a large diameter propeller fan.



DC fan motor

The outdoor unit utilises a miniaturised, high efficiency, multi-stage DC fan motor.



Large heat exchanger

Heat exchanger performance is substantially improved by the mounting of a 2-row large heat exchanger.




DC inverter control

Efficiency is improved through the use of a new active filter module.



Subcool heat exchanger

Cooling performance is improved by utilising a dual tube heat exchanger.



Scroll compressor



The scroll compressor has a wide range of rotational frequencies from 15 to 120 rps. Fujitsu General's unique sensorless sine wave control method enables smooth control of the input power into the motor contributing to the improvement of the energy efficiency operating characteristics and the low sound operation.

15-120 rps



Long piping capability

Our advanced refrigerant control technology allows us to achieve a total refrigerant piping length of 400m.



Up to 22 connectable units

A new outdoor unit with the optimum heat exchanger structure enables the connection of up to 22 indoor units.


High static pressure

External static pressure is available up to 30 Pa. (only 12HP)



Low noise characteristics

Highly suited to densely populated areas due to the low operating sound.



Specifications

Rating capacity range		HP	8	10	12
Model name			AJY072LELAH	AJY090LELAH	AJY108LELAH
Maximum connectable indoor units			1-15	1-19	1-22
Power source			3-phase, ~400V, 50Hz		
Capacity	Cooling	kW	22.4	28.0	33.5
	Nominal heating		22.4	28.0	33.5
	Max heating		25.0	31.5	37.5
Input power	Cooling	kW	6.30	8.59	10.42
	Nominal heating		4.65	6.61	8.18
	Max heating		5.45	8.29	10.25
EER	Cooling	W/W	3.56	3.26	3.22
COP	Nominal heating		4.82	4.24	4.10
	Max heating		4.56	3.80	3.66
Air flow rate		m ³ /h	8,400	9,000	11,000
External static pressure (max.)		Pa	20	30	30
Sound pressure level / Power level	Cooling	dB (A)	52 / 66	54/69	59/73
	Heating		54 /-	57/-	61/-
Dimensions	Height	mm	1,428	1,428	1,428
	Width		1,080	1,080	1,080
	Depth		480	480	480
Weight		kg	170	177	178
Refrigerant	Type		R410A	R410A	R410A
	Charge	kg (CO ₂ eq-1)	7.0 (14.6)	7.5 (15.7)	7.5 (15.7)
Connection pipe diameter	Liquid	mm	9.52	9.52	12.70
	Gas		19.05	22.20	28.58
Total pipe length		m	400	400	400
Max. Height difference			50/40 (Outdoor unit: Upper/Lower)		
Operation range	Cooling	°C	-15 to 46	-15 to 46	-15 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.

Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.


Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m.

Dimensions

Models: AJY072LELAH / AJY090LELAH / AJY108LELAH

(Unit: mm)



HEAT PUMP TYPE

AIRSTAGE™ J-III series

Fujitsu General provides air conditioning systems for a wide range of applications from small office buildings and stores to large houses and apartments.

System Outline


High energy efficiency

Heat pump inverter control is used to achieve efficient cooling or heating operation with any indoor unit combination.

Flexible systems for small and medium size building air conditioning requirements


The space saving and long piping design allows for flexible installation on roofs or balconies of small and medium size buildings. Multiple indoor units of various capacities and types can be connected.

Small Office



System configuration example

- This system typically used for small and medium-sized buildings
- This example shows the connection of multiple indoor units using separation tubes and headers




Features

Efficiency during operation

The high COP is achieved for all models through a large heat exchanger, high efficient DC twin compressor and our own technologies.

High EER / COP

Single phase



6HP class



Advanced high efficiency technology




Large propeller fan

High performance and low noise is realised by the large propeller and angle optimisation.



DC fan motor

The outdoor unit utilises a miniaturised, high efficiency, multi-stage DC fan motor.



Large heat exchanger

Heat exchange performance is substantially improved by inclusion of a 3-row large heat exchanger.




DC inverter control

Efficiency is improved through the new active filter module.



Subcool heat exchanger


Cooling performance is improved from the dual tube heat exchanger.



High efficiency compressor motor


Optimised refrigerant flow design

High precision parts




DC twin rotary compressor

Efficiency in all load regions is consistent, especially when meeting low to medium load requirements.



Long piping capability

Our advanced refrigerant control technology allows us to achieve a total refrigerant piping length of 180m opening up new possibilities in system design.



Specifications


Rating capacity range		HP	4	5	6
Model name			AJY040LBLAH	AJY045LBLAH	AJY054LBLAH
Maximum connectable indoor units			1-8	1-9	1-10
Power source			Single-phase, ~230V, 50Hz		
Capacity	Cooling	kW	12.1	14.0	15.5
	Heating	kW	13.6	16.0	18.0
Input power	Cooling	kW	2.90	3.57	4.18
	Heating	kW	2.80	3.55	4.26
EER	Cooling	W/W	4.17	3.92	3.71
COP	Heating	W/W	4.86	4.51	4.23
Air flow rate		m ³ /h	6,200	6,400	6,900
Sound pressure level / Power level	Cooling	dB (A)	50 / 66	51 / 67	53 / 69
	Heating	dB (A)	52 / 68	53 / 69	55 / 71
Heat exchanger fin			Blue fin	Blue fin	Blue fin
Dimensions	Height	mm	1,334	1,334	1,334
	Width	mm	970	970	970
	Depth	mm	370	370	370
Weight		kg	117	117	119
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	kg (CO ₂ eq-l)	4.8 (10.0)	5.3 (11.1)	5.3 (11.1)
Connection pipe diameter	Liquid	mm	9.52	9.52	9.52
	Gas	mm	15.88	15.88	19.05
Total pipe length		m	180	180	180
Max. height difference			50/40 (Outdoor unit: Upper/Lower)		
Operation range	Cooling	°C	-5 to 46	-5 to 46	-5 to 46
	Heating	°C	-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m.
The protective function may work when using it outside the operation range.

Dimensions


Models: AJY040LBLAH / AJY045LBLAH / AJY054LBLAH

(Unit: mm)




Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



Easier installation

With the connection check function it is possible to confirm whether the wiring connection and address settings are correct through a quick check run function.



HEAT PUMP TYPE

AIRSTAGE™ J-IIS series

Fujitsu General provides air conditioning systems for a wide range of applications from small office buildings and stores to large houses.

System Outline

Space saving and low sound level design

Compact design and high efficiency is realised by ALL-DC technology, large capacity DC twin rotary compressor and a 3-row heat exchanger.


Flexible systems for small and medium building air conditioning requirements

Due to the compact size and flexible piping design, the J-IIS series can be installed easily when the installation space is limited such as in homes, shops and small offices. Multiple indoor units of various capacities and types can be connected.

Large Homes




System configuration example




Features

Easy transportation and flexible installation




Small and light weight outdoor unit

This model is much more compact than conventional 6HP comparable outdoor units. Even when installed on the balcony it fits within the height of the railing. The compact size with a height of less than 1m allows it to be installed in tight spaces.



High AEER* and ACOP*

High average cooling and heating efficiency are significantly realised by utilising All DC inverter control, DC twin rotary compressor, and advanced airflow structure.



*AEER: Average Energy Efficiency Ratio
*ACOP: Average Coefficient Of Performance


Advanced high efficiency technology




Large propeller fan
High performance and low noise realised by the large propeller and angle optimisation.



DC fan motor
The outdoor unit utilises a miniaturised, high efficiency, multi-stage DC fan motor.



Large heat exchanger
Heat exchange performance is substantially improved by the use of 3-row large heat exchanger.



High heat transfer copper tube (Improved lead angle)




DC inverter control
Efficiency is improved through the new active filter module.




Compact and high performance DC twin rotary compressor

Efficiency in all load regions particularly when at low to medium load requirements.




Smooth airflow grille
Aerodynamically designed for enhanced efficiency with little blow loss.




Long piping capability

Our advanced refrigerant control technology allows us to achieve a total refrigerant piping length of 80m. This opens up new possibilities in system design.




Non stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



Easier installation

With the connection check function it is possible to confirm whether the wiring connection and address settings are correct through a quick check run function.



Specifications


Rating capacity range		HP	4	5	6	
Model name			AJT040LCLAH	AJT045LCLAH	AJT054LCLAH	
Maximum connectable indoor units			7	8	8	
Power source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	12.1	14.0	15.1	
	Heating	kW	13.6	16.0	16.5	
Input power	Cooling	kW	3.44	4.23	4.58	
	Heating	kW	3.09	3.93	4.11	
EER	Cooling	W/W	3.52	3.31	3.30	
	Heating	W/W	4.40	4.07	4.01	
Air flow rate	Cooling	m³/h	4,040 (1,122)	4,200 (1,167)	4,540 (1,261)	
	Heating	(l/s)	4,040 (1,122)	4,200 (1,167)	4,200 (1,167)	
Sound pressure level / Power level	Cooling	dB (A)	51	53	56	
	Heating	dB (A)	54	55	56	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	
Dimensions	Height	mm	998	998	998	
	Width	mm	970	970	970	
	Depth	mm	370	370	370	
Weight			kg	86	87	
	Refrigerant		Type (Global Warming Potential)	R410A(2,088)	R410A(2,088)	R410A(2,088)
		Charge	kg (CO2eq-T)	4.0(8.4)	4.0(8.4)	4.0(8.4)
Connection pipe diameter	Liquid	mm	9.52	9.52	9.52	
	Gas	mm	15.88	15.88	15.88	
Total pipe length		m	80	80	80	
Max. Height difference		m	30	30	30	
Operation range	Cooling	°C	-5 to 46	-5 to 46	-5 to 46	
	Heating	°C	-20 to 21	-20 to 21	-20 to 21	

Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m.
 These are the measured values in the manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

Dimensions

Models: AJT040LCLAH / AJT045LCLAH / AJT054LCLAH

(Unit: mm)



AIRSTAGE™ INDOOR UNITS

17 types and 82 models available to meet the requirements of almost any building design.

The AIRSTAGE™ indoor units were developed to be highly efficient, compact, low noise producing with user friendly operation. With a variety of indoor units and capacities available, Fujitsu General has an indoor unit to match any requirement which is easy to install and maintain.

INDOOR UNITS LINEUP

4-way Flow Compact Cassette

4-way Flow Cassette

Circular Flow Cassette

Mini Duct

Slim Duct / Slim Concealed Floor

Medium Static Pressure Duct

High Static Pressure Duct

Compact Floor

Floor / Ceiling

Ceiling

Wall Mounted (EEV Internal / External)



INDOOR UNITS LINEUP

Comprehensive range of indoor units with varied design and capacity ranges are available which can be selected to suit most air conditioning needs. 17 types, 82 models, with a capacity range from 2.2kW to 28.0kW

Indoor units range

Model code	7	9	12	14	18	24	30	34	36	45	54	60	72	90	96	
Capacity range (kW)	2.2	2.8	3.6	4.5	5.6	7.1	9.0	10.0	11.2	12.5	14.0	18.0	22.4	25.0	28.0	
Cassette	4-way Flow Compact															
	4-way Flow	(Slim type)														
		(Large type)														
	Circular Flow NEW	(Slim type)														
(Large type)																
Duct	Mini Duct (With drain pump)															
	Slim Duct (With drain pump)															
	Medium Static Pressure Duct															
	High Static Pressure Duct															
Floor	Floor (Same as Ceiling models)															
	Slim Concealed Floor (Same as Slim Duct models)															
	Compact Floor NEW															
	Compact Floor NEW (EEV external)					With this model, connection of EV kit is necessary.										
Ceiling	Ceiling															
Wall Mounted	Wall Mounted NEW															
	Wall Mounted NEW (EEV external)					With this model, connection of EV kit is necessary.										

*1: ARXC60/72/90/96G cannot be connected to J-IIS series and J-III series.

4-way Flow Compact Cassette

Models

- AUXB07GALH
- AUXB09GALH
- AUXB12GALH
- AUXB14GALH
- AUXB18GALH
- AUXB24GALH




Features

2-stage turbo fan

High efficiency design through 2-stage structure

Air distribution evenly spread across the heat exchanger is possible due to the new 2-stage turbo fan which produces two separate airflow streams.




Previous turbo fan
In the case of a previous fan, the air outlet range was narrow as the airflow moved to the motor side which meant the velocity of air passing through the heat exchanger was uneven.


Quiet operation

Optimisation of wing form (laminar wing type) and wing number (7 blades each)

Designed by CFD-analysis (fluid) simulations



Improvement of the airflow distribution



1 Maintenance of fan motor and fan

Maintenance of the fan motor and fan can be done easily after taking off the panel as the bell mouth of the fan can be removed easily.

- A: Fan motor
- B: 2-stage turbo fan
- C: Bell-mouth
- D: Panel

2 Air filter: standard equipment

3 Adaptation of transparent drainage parts

During installation, maintenance and operation, the drain pump and kit can be checked easily.

High ceiling mode


The compact cassette can be installed up to a height of 3.0m (12/14/18/24).

Model code	The maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
07	2.7	-
09	2.7	-
12	2.7	3.0
14	2.7	3.0
18	2.7	3.0
24	2.7	3.0




Compact design

The worlds first 24,000Btu model in the compact cassette category. (Easily installed by taking off ceiling panel of 600 x 600 size)



High lift drain pump



Optional parts

- Air outlet shutter plate: UTR-YDZB
- Insulation kit for high humidity: UTZ-KXGC
- Fresh air intake kit: UTZ-VXAA

Specifications

Model name			AUXB07GALH	AUXB09GALH	AUXB12GALH	AUXB14GALH	AUXB18GALH	AUXB24GALH
Power source			Single - phase, ~230V, 50Hz					
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating		2.8	3.2	4.1	5.0	6.3	8.0
Input power	W		25	25	29	35	36	84
Airflow rate	High	m ³ /h (l/s)	540 (150)	550 (153)	600 (167)	680 (189)	710 (197)	1,030 (286)
	Med		450 (125)	450 (125)	530 (147)	590 (164)	580 (161)	830 (231)
	Low		350 (97)	350 (97)	390 (108)	390 (108)	400 (111)	450 (125)
Sound pressure level	High	dB (A)	34	35	37	38	41	50
	Med		30	30	34	34	35	44
	Low		25	25	27	27	27	30
Dimensions (H x W x D)	mm		245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570
Weight	kg		15	15	15	15	17	17
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	6.35	9.52	9.52
	Gas (Flare)		12.70	12.70	12.70	12.70	15.88	15.88
Drain hose diameter (I.D./O.D.)			25 / 32					
Cassette grille	Model name		UTG-UFYC-W					
	Dimensions (HxWxD)	mm	50 x 700 x 700					
	Weight	kg	2.6					


Note: Specifications are based on the following conditions.

Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.

Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)



4-way Flow Cassette

Models (Slim type)
AUXD18GALH
AUXD24GALH




Models (Large type)
AUXA18GALH
AUXA24GALH
AUXA30GALH
AUXA34GALH
AUXA36GALH
AUXA45GALH
AUXA54GALH



Features


High efficiency turbo fan with 3-dimensional blade

High efficiency airflow distribution has been achieved by the introduction of a 3 dimensional blade which increases the air passing over the heat exchanger.




Improvement of the airflow distribution

The unique design of the louvers and added space between the chassis and ceiling maximises airflow distribution within the room.



Adjustment of hanger position is possible after installation




High ceiling mode


This cassette can be installed up to a height of 4.2m (36/45/54).

Model code	The maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
18	3.0	3.5
24	3.0	3.5
30	3.2	3.6
34	3.2	3.6
36	3.2	4.2
45	3.2	4.2
54	3.2	4.2

One way installation



High lift drain pump



Optional parts

IR receiver unit:	UTY-LRHYB1
Air outlet shutter plate:	UTR-YDZK
Panel spacer:	UTG-BKXA-W
Insulation kit for high humidity:	UTZ-KXRA
Wide panel:	UTG-AKXA-W
Fresh air intake kit:	UTZ-VXRA


Specifications

Model name	AUXD18GALH	AUXD24GALH	AUXA18GALH	AUXA24GALH	AUXA30GALH	AUXA34GALH	AUXA36GALH	AUXA45GALH	AUXA54GALH	
Power source	Single - phase, ~230V, 50Hz									
Capacity	Cooling	5.6	7.1	5.6	7.1	9.0	10.0	11.2	12.5	14.0
	Heating	6.3	8.0	6.3	8.0	10.0	11.2	12.5	14.0	16.0
Input power	W	39	46	51	51	59	77	80	99	119
Airflow rate	High	1,150 (319)	1,280 (356)	1,420 (394)	1,420 (394)	1,600 (444)	1,750 (486)	1,800 (500)	1,900 (528)	2,000 (556)
	Med	940 (261)	1,040 (289)	1,230 (342)	1,230 (342)	1,300 (361)	1,300 (361)	1,300 (361)	1,370 (381)	1,370 (381)
	Low	870 (242)	870 (242)	1,100/1,000*(306/278)	1,100/1,000*(306/278)	1,100 (306)	1,100 (306)	1,100 (306)	1,100 (306)	1,100 (306)
Sound pressure level	High	36	38	40	40	40	43	44	46	47
	Med	30	33	36	36	38	38	39	39	39
	Low	29	29	33/31*	33/31*	33	33	33	33	33
Dimensions (H × W × D)	mm	246 × 840 × 840	246 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840
Weight	kg	22	22	27	27	27	27	27	27	27
Connection pipe diameter	Liquid (Flare)	9.52	9.52	9.52	9.52	9.52	9.52	9.52	9.52	9.52
	Gas (Flare)	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05
Drain hose diameter (I.D./O.D.)		25 / 32								
Cassette grille	Model name	UTG-UGYA-W								
	Dimensions (H×W×D)	50 × 950 × 950								
	Weight	5.5								

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

*1: This value is under cooling operation.

Dimensions (Unit: mm) (): AUXD18 / AUXD24



Circular Flow Cassette

Models (Slim type)

- AUXM18GLAH **NEW**
- AUXM24GLAH **NEW**
- AUXM30GLAH **NEW**



Models (Large type)


- AUXK18GLAH **NEW**
- AUXK24GLAH **NEW**
- AUXK30GLAH **NEW**
- AUXK34GLAH **NEW**
- AUXK36GLAH **NEW**
- AUXK45GLAH **NEW**
- AUXK54GLAH **NEW**



Features


Unique circular flow design

The new cassette type creates a consistent and even temperature via multi-directional 360° airflow functionality. This is achieved by mounting a high performance DC fan motor, new turbo fan and unique seamless airflow louver design.



Uniform temperature air conditioning

Achieve a consistent and even temperature in the room with circular flow and wide vertical airflow spreading conditioned air to every corner of the room.



Individual louver control

Each louver can be set individually with the Touch Panel Wired Remote Controller allowing different directional airflows according to various room layouts.

* Touch Panel Wired RC (UTY-RNRYZ2) only



Comfortable air conditioning by preventing direct blowing of cold air and by providing swinging air flow simultaneously.



Efficient air conditioning based on the room layout

Human sensor increases energy saving operation

Energy saving operation starts automatically by detecting the motion of a person. The human sensor detects movement and activates or deactivates energy saving mode accordingly. 2 modes of save operation mode and stop mode can be selected.

*Touch Panel Wired RC (UTY-RNRYZ2) only



Human sensor (Option)

2 modes can be selected.

- Auto saving** Power is saved while people are away.
- Auto OFF** Operation stops after people go out.



Specifications


Model name	AUXM018GLAH	AUXM024GLAH	AUXM030GLAH	AUXK018GLAH	AUXK024GLAH	AUXK030GLAH	AUXK034GLAH	AUXK036GLAH	AUXK045GLAH	AUXK054GLAH	
Power source	Single - phase, ~230V, 50Hz										
Capacity	Cooling	5.6	7.1	9.0	5.6	7.1	9.0	10.0	11.2	12.5	14.0
	Heating	6.3	8.0	10.0	6.3	8.0	10.0	11.2	12.5	14.0	16.0
Input power	W	20	25	49	40	40	47	47	61	89	116
Airflow rate	High	1,050	1,120	1,470	1,420	1,420	1,440	1,440	1,620	1,820	2,040
	Med-Hi	930	1,050	1,160	1,360	1,360	1,400	1,400	1,500	1,590	1,800
	Med	900	930	1,070	1,300	1,300	1,340	1,340	1,400	1,500	1,590
	Lo-Hi	870	900	930	1,270	1,270	1,300	1,300	1,340	1,400	1,440
	Low	810	870	900	1,200	1,200	1,280	1,280	1,280	1,300	1,300
Sound pressure level	Quiet	780	780	780	1,150	1,150	1,150	1,150	1,150	1,150	1,150
	High	33	35	40	38	38	39	39	41	44	47
	Med-Hi	32	33	36	37	37	38	38	40	42	45
	Med	31	32	34	36	36	37	37	38	40	42
	Lo-Hi	30	31	32	35	35	36	36	37	38	39
Low	29	30	31	34	34	35	35	35	36	36	
	Quiet	28	28	28	33	33	33	33	33	33	
Dimensions (H × W × D)	mm	246×840×840	246×840×840	246×840×840	288×840×840	288×840×840	288×840×840	288×840×840	288×840×840	288×840×840	288×840×840
Weight	kg	24.0	24.5	24.5	26.5	26.5	29.5	29.5	29.5	29.5	29.5
Connection pipe diameter	Liquid (Flare)	6.35	9.52	9.52	6.35	6.35	9.52	9.52	9.52	9.52	9.52
	Gas (Flare)	12.70	15.88	15.88	12.70	12.70	15.88	15.88	15.88	15.88	15.88
Drain hose diameter (I.D./O.D.)		25 / 32									
Cassette Grille	Model name	UTG-UKGC-W									
	Dimensions (H×W×D)	53×950×950									
	Weight	6.0									

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / 15°CWB, and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.




When AUX*018GLAH is connected to the outdoor unit other than J-III, pipe diameter should be Ø9.52/Ø15.88 (Liq/Gas)
When AUXK036GLAH, AUXK045GLAH, and AUXK054GLAH are connected to the outdoor unit other than J-III, gas pipe diameter should be Ø19.05.

Dimensions (Unit: mm)

Models: AUXM18 / AUXM24 / AUXM30



Models: AUXK18 / AUXK24 / AUXK30 / AUXK34 / AUXK36 / AUXK45 / AUXK54



Mini Duct

Models (With drain pump)


- ARXK07GCLH
- ARXK09GCLH
- ARXK12GCLH
- ARXK14GCLH
- ARXK18GCLH
- ARXK24GCLH



Features


Compatible with the requirements of the installation space

- The compact design allows for the installation space to be reduced down to a minimum depth of 450mm and height of 198mm
- Lightweight: 16kg, 10% down



Optimum airflow path and low noise operation

Low noise is realised drastically with the stabilized airflow design



Easy design and maintenance for drain

By using the DC fan motor, it is possible to change the static pressure range from 0 to 50 Pa*.

The change of static pressure range is possible by the remote controller.

* 0 to 30 Pa. (07/09/12)

Built-in drain pump as standard:
Maintenance is easy




Parts can be replaced from the side of the body where maintenance is easier

6-speed control*

Multistep airflow speed control allows this model to be installed in quiet areas.


Low noise
21 dB(A)
at 04 model



* Compatible remote controllers:
UTY-RNRY22 / UTY-RSRY / UTY-RHRY / UTY-DCGY / UTY-DTGYZ1 / UTY-ALGXZ1 / UTY-APGXZ1

Auto louver grille kit (Option)

- Thin design provides a comfortable living environment over a wide area
- Automatic louver grille provides comfortable air conditioning from floor to ceiling (Optional)



Optional parts

- Remote sensor unit: UTY-XSZX
- IR receiver unit: UTB-TWC
- Auto louver grille kit: UTD-GXTA-W (for ARXK04/07/09/12/14)
UTD-GXTB-W (for ARXK18)
UTD-GXTC-W (for ARXK24)

Specifications

Model name			ARXK07GCLH	ARXK09GCLH	ARXK12GCLH	ARXK14GCLH	ARXK18GCLH	ARXK24GCLH
Power source			Single - phase, ~230V, 50Hz					
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	kW	2.8	3.2	4.0	5.0	6.3	8.0
Input power	GCLH	W	28	28	35	66	73	80
Airflow rate	High	m ³ /h	460(128)	460(128)	550(153)	760(211)	930(258)	1,160(322)
	Med-H		-	-	-	-	-	-
	Med		420(117)	420(117)	480(133)	560(156)	740(206)	960(267)
	Med-L		-	-	-	-	-	-
	Low		370(103)	370(103)	410(114)	410(114)	540(150)	750(208)
Quiet		-	-	-	-	-	-	
Static pressure range			0 to 30	0 to 30	0 to 30	0 to 50	0 to 50	0 to 50
Standard static pressure			10	10	10	15	15	15
Sound pressure level	High	Pa	26	26	29	34	33	32
	Med-H		-	-	-	-	-	-
	Med		24	24	26	28	28	28
	Med-L		-	-	-	-	-	-
	Low		22	22	24	24	24	25
Quiet		-	-	-	-	-	-	
Dimensions (H × W × D)	mm		198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450	198 × 1,100 × 450
Weight	kg		15.5	15.5	16	16	19	22.5
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	6.35	9.52	9.52
	Gas (Flare)		12.70	12.70	12.70	12.70	15.88	15.88
Drain hose diameter (I.D./O.D.)			25 / 32					

Note: Specifications are based on the following conditions.


Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating: Indoor temperature of 20°CDB / 15°CWB, and outdoor temperature of 7°CDB / 6°CWB.

Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)


Models: ARXK07GCLH / ARXK09GCLH / ARXK12GCLH / ARXK14GCLH



- ① Refrigerant pipe flare connection (Liquid)
- ② Refrigerant pipe flare connection (Gas)
- ③ Drain hose connection

	ARXK07-14	ARXK18	ARXK24
A	P100-6-600	P100-8-800	P100-10-1000
B	650	850	1050
C	752	952	1152
D	650	850	1050
E	665	864	1064
F	700	900	1100

Models: ARXK18GCLH / ARXK24GCLH



- ① Refrigerant pipe flare connection (Liquid)
- ② Refrigerant pipe flare connection (Gas)
- ③ Drain hose connection

	ARXK07-14	ARXK18	ARXK24
A	P100-6-600	P100-8-800	P100-10-1000
B	650	850	1050
C	752	952	1152
D	650	850	1050
E	665	864	1064
F	700	900	1100

Slim Duct / Slim Concealed Floor

Models (With drain pump)


- ARXD07GALH
- ARXD09GALH
- ARXD12GALH
- ARXD14GALH
- ARXD18GALH
- ARXD24GALH



Features

Slim design

With a slim indoor design, this indoor unit can be installed in narrow ceiling spaces.



Selectable static pressure


By using DC fan motor, it is possible to change the static pressure range from 0 to 90Pa. The static pressure range is configurable through the remote controller.



Static pressure range
0 to 90 Pa

*24 model is 0 to 50Pa


High lift drain pump



Drain hose (Standard accessory)


Air-intake

Air intake direction can be selected to match the installation site.



Flexible installation

Ceiling concealed




Floor concealed




Filter (Accessory)

ARXD07 / 09 / 12 / 14 / 18




ARXD24



Auto louver grille kit (Option)

The Auto louver grille will provide comfortable airflow and compliment luxury interiors.



Optional parts

- Remote sensor unit: UTY-XSZX
- IR receiver unit: UTB-TWC
- Auto louver grille kit: UTD-GXTA-W (for ARXD04/07/09/12/14GALH)
- UTD-GXTB-W (for ARXD18GALH)
- UTD-GXTC-W (for ARXD24GALH)

Specifications

Model name	ARXD07GALH	ARXD09GALH	ARXD12GALH	ARXD14GALH	ARXD18GALH	ARXD24GALH
Power source	Single - phase, ~230V, 50Hz					
Capacity	Cooling	2.2	2.8	3.6	4.5	5.6
	Heating	2.8	3.2	4.0	5.0	6.3
Input power	44	50	54	92	83	122
Airflow rate	High	550 (153)	600 (167)	600 (167)	800 (222)	940 (261)
	Med	490 (136)	550 (153)	510 (142)	710 (197)	840 (233)
	Low	440 (122)	480 (133)	450 (125)	610 (169)	750 (208)
Static pressure range	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50
Standard static pressure	25	25	25	25	25	25
Sound pressure level	High	28	29	30	34	35
	Med	25	26	27	32	32
	Low	22	24	24	28	28
Dimensions (H × W × D)	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 900 × 620	198 × 1,100 × 620
Weight	17	17	18	18	22	26
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	9.52
	Gas (Flare)	12.70	12.70	12.70	12.70	15.88
Drain hose diameter (I.D./O.D.)	25 / 32					

Note: Specifications are based on the following conditions.


Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.

Heating: Indoor temperature of 20°CDB / 15°CWB, and outdoor temperature of 7°CDB / 6°CWB.

Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)

*Service accessibility must be allowed for when installing the product. Please consult the installation manual for the necessary service access size.



	ARXD07-14	ARXD18	ARXD24
A	700	900	1100
B	650	850	1050
C	734	934	1134
D	650	850	1050
E	P100x6=600	P100x8=800	P100x10=1000
F	-	22xØ5	26xØ5
G	574	774	974

Medium Static Pressure Duct

Models


- ARXA24GBLH
- ARXA30GBLH
- ARXA36GBLH
- ARXA45GBLH



Features


Slim and compact design

In the case of bottom return air connection, not only does the indoor unit design allow for installation in a narrow ceiling space of up to 270mm, further space savings have been achieved by mounting the electrical control box internally inside the chassis.



Low energy consumption through the high efficiency DC fan motor

Improved motor efficiency compared to the previous model.



Can be installed in various locations

This unit can be installed in a range of locations such as high-rise apartments through low static pressure design.



It can also be installed in open spaces where higher static pressure is required, such as offices.




Selectable with a wide range of static pressure

It is possible to change the static pressure range from 0 to 150Pa.

Static pressure range
0 to 150 Pa


Easy maintenance

See below for the case of rear suction type



Structural improvement is attained by making the bottom panel two pieces, front and rear. The internal fan casing is also manufactured in two pieces, namely upper and lower. The maintenance of the motor and fan can be easily carried out by removing the rear panel and the lower part of the casing while leaving the main chassis installed.

Two direction drain piping




Static pressure setting via the remote controller

Changing the static pressure range is possible with the remote controller




Installation styles

Embedded in Ceiling



Hanging from Ceiling



Optional parts

- Remote sensor unit: UTY-XSZX
- Long life filter: UTD-LF25NA
- Flange (square): UTD-SF045T
- Flange (round): UTD-RF204
- IR receiver unit: UTB-TWC
- Drain pump unit: UTZ-PX1NBA


Specifications

Model name			ARXA24GBLH	ARXA30GBLH	ARXA36GBLH	ARXA45GBLH
Power source			Single - phase, ~230V, 50Hz			
Capacity	Cooling	kW	7.1	9.0	11.2	12.5
	Heating		8.0	10.0	12.5	14.0
Input power		W	94	108	194	240
Airflow rate	High	m ³ /h (l/s)	1,280 (356)	1,410 (392)	1,840 (511)	1,970 (547)
	Med		990 (275)	1,280 (356)	1,600 (444)	1,860 (517)
	Low		840 (233)	1,150 (319)	1,470 (408)	1,640 (456)
Static pressure range		Pa	0 to 150	0 to 150	0 to 150	0 to 150
Standard static pressure			40	50	50	60
Sound pressure level	High	dB (A)	31	34	37	41
	Med		27	32	35	38
	Low		23	29	33	36
Dimensions (H × W × D)		mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
Weight		kg	36	40	40	40
Connection pipe diameter	Liquid (Flare)	mm	9.52	9.52	9.52	9.52
	Gas (Flare)		15.88	15.88	19.05	19.05
Drain hose diameter (I.D./O.D.)			25 / 32			

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)

*Service accessibility must be allowed for when installing the product. Please consult the installation manual for the necessary service access size.



- ① Refrigerant piping flare connection (Liquid) :
- ② Refrigerant piping flare connection (Gas) :
- ③ Drain piping connection (Drain pipe)

High Static Pressure Duct

Models

ARXC36GBTH
ARXC36GATH
ARXC45GATH
ARXC60GATH



Models

ARXC72GATH
ARXC90GATH



Models


ARXC96GATH



Features

Static pressure selection


By using a DC fan motor, it is possible to change the static pressure range from 0 to 200Pa (ARXC36GBTH) / 300Pa (ARXC96).



Low noise

Models: ARXC36 / ARXC45 / ARXC60


Cutting off the corners of the conventional indoor unit front panel and fan casing, has enabled less turbulent air flow. Low noise is realised by adopting a plastic case and a plastic fan.



New model
(ARXC36GBTH)


ARXC36GBTH: Plastic fan [42dB(A)]

* Model: Material
(At 100Pa: Actual noise measurement value)




Low energy consumption with high efficiency DC fan motor

Improved motor efficiency from previous model.



Easy installation (compact size and lightweight)

A compact size and lightweight indoor unit has been developed by reducing the basic chassis and the overall material weight.



Optional parts

Long-life filter: UTD-LF60KA (For ARXC36 / 45 / 60)
IR receiver unit: UTB-TWC
Remote sensor unit: UTY-XSZX

Specifications

Model name	ARXC36GBTH	ARXC36GATH	ARXC45GATH	ARXC60GATH*	ARXC72GATH*	ARXC90GATH*	ARXC96GATH*
Power source	Single - phase, ~230V, 50Hz						
Capacity	Cooling	11.2	11.2	12.5	18.0	22.4	28.0
	Heating	12.5	12.5	14.0	20.0	25.0	31.5
Input power	207	405	715	730	1,110	1,250	838
Airflow rate	High	1,900 (553)	2,600 (722)	3,500 (972)	3,500 (972)	3,900 (1,083)	4,850 (1,347)
	Med	1,680 (467)	1,950 (542)	3,000 (833)	3,000 (833)	3,300 (917)	4,250 (1,181)
	Low	1,330 (369)	1,450 (403)	2,460 (683)	2,460 (683)	3,000 (833)	3,600 (1,000)
Static pressure range	0 to 200	100 to 200	100 to 250	100 to 250	50 to 300	100 to 300	0 to 300
Standard static pressure	100	100	100	100	260	250	150
Sound pressure level	High	42	45	49	49	51	48
	Med	36	38	45	45	48	45
	Low	32	32	42	42	45	42
Dimensions (H × W × D)	400 × 1,050 × 500	400 × 1,050 × 500	400 × 1,050 × 500	400 × 1,050 × 500	450 × 1,550 × 700	450 × 1,550 × 700	550 × 1,587 × 700
Weight	40	43	46	46	83	85	105
Connection pipe diameter	Liquid	9.52 (Flare)	9.52 (Flare)	9.52 (Flare)	9.52 (Flare)	12.70 (Brazing)	12.70 (Brazing)
	Gas	19.05 (Flare)	19.05 (Flare)	19.05 (Flare)	19.05 (Flare)	22.22 (Brazing)	22.22 (Brazing)
Drain hose diameter (I.D./O.D.)	25 / 32						


Note: Specifications are based on the following conditions.

Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.


*: ARXC60/72/90/96 cannot be connected to J-IIS or J-III series.

Dimensions (Unit: mm)


Models: ARXC36 / ARXC45 / ARXC60



Models: ARXC72 / ARXC90



Models: ARXC96



- ① Refrigerant piping flare connection (Liquid)
- ② Refrigerant piping flare connection (Gas)
- ③ Drain piping connection

- ① Refrigerant pipe flare connection (Liquid)
- ② Refrigerant pipe flare connection (Gas)
- ③ Drain hose

- ① Refrigerant pipe flare connection (Liquid)
- ② Refrigerant pipe flare connection (Gas)
- ③ Drain hose

Compact floor



- | | |
|------------------------------|------------------------------|
| Models (EEV internal) | Models (EEV external) |
| AGYA007GCAH NEW | AGYE007GCAH NEW |
| AGYA009GCAH NEW | AGYE009GCAH NEW |
| AGYA012GCAH NEW | AGYE012GCAH NEW |
| AGYA014GCAH NEW | AGYE014GCAH NEW |



Features


2 fan and wide airflow

Individual vertical airflow by 2 fans can control the whole room comfortably.



Flexible and easy installation

Due to compact and flexible methods for installation including, floor, concealed, half concealed, or wall mounted, installation approach can be modified to match the room layout.




Specifications

Model name		AGYA007GCAH	AGYA009GCAH	AGYA012GCAH	AGYA014GCAH	AGYE007GCAH	AGYE009GCAH	AGYE012GCAH	AGYE014GCAH
Power source		Single - phase, ~230V, 50Hz							
Capacity	Cooling	2.2	2.8	3.6	4.0	2.2	2.8	3.6	4.0
	Heating	2.8	3.2	4.0	4.5	2.8	3.2	4.0	4.5
Input power		16	17	22	29	16	17	22	29
		W							
Airflow rate	High	470	500	590	670	470	500	590	670
	Med-H	420	450	520	590	420	450	520	590
	Med	390	400	470	520	390	400	470	520
	Med-L	360	360	420	450	360	360	420	450
	Low	330	330	390	390	330	330	390	390
	Quiet	270	270	340	340	270	270	340	340
Sound pressure level	High	37	38	42	46	37	38	42	46
	Med-H	35	36	39	42	35	36	39	42
	Med	33	34	37	39	33	34	37	39
	Med-L	31	31	35	36	31	31	35	36
	Low	29	29	33	33	29	29	33	33
Quiet	22	22	30	30	22	22	30	30	
Dimensions (H x W x D)	mm	600×740×200	600×740×200	600×740×200	600×740×200	600×740×200	600×740×200	600×740×200	600×740×200
Weight	kg	15.0	15.0	15.0	15.0	14.5	14.5	14.5	14.5
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)	9.52	9.52	12.70	12.70	9.52	9.52	12.70	12.70
Drain hose diameter (I.D./O.D.)		13.8 / 15.8 to 16.7							
EV Kit (option)		-	-	-	-	UTR-EV09XB	UTR-EV09XB	UTR-EV14XB	UTR-EV14XB

Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

When AGY*007GCAH and AGY*009GCAH are connected to the outdoor unit other than J-III, gas pipe diameter should be Ø12.70.

Dimensions (Unit: mm)



Quiet operation

Quiet operation is realized by 6 fan speed control. (via 2 wire controller)

Low noise
22 dB(A)


at 007/009 models



* Compatible Remote Controller is as follows:
 UTY-RNRY22 / UTY-RSRY / UTY-RHRY / UTY-DCGY / UTY-DTGYZ1 / UTY-ALGXZ1 / UTY-APGXZ1

Flexible piping connection

Drain hose and piping can be drawn flexibly in the right, left, side, and down directions



Ceiling

Models

- ABYA30GATH
- ABYA36GATH
- ABYA45GATH
- ABYA54GATH



Features

Installation

Open

General installation pattern which suspends the indoor unit from the ceiling.

Concealed

Installation pattern where part of the indoor unit is embedded into the ceiling.

Wall mounted
(Field supplied)

Installation which fixes the indoor unit to the wall by the use of wall brackets (Field supplied). This type of installation can be used when the ceiling space is insufficient.

Double auto swing and wide airflow

Auto airflow direction and auto swing

Right and left


5 steps selectable

Up and down

4 steps selectable

Long airflow

Long airflow ensures comfort to every corner of a large room.




High power DC fan motor


- High power
- Wide rotation range
- High efficiency



Fresh air intake




Slim and Compact design



High lift drain pump

Optional drain pump unit allows flexible installation design.



Optional parts


- Drain pump unit: UTR-DPB24T
- Flange: UTD-RF204

Specifications

Model name			ABYA30GATH	ABYA36GATH	ABYA45GATH	ABYA54GATH
Power source			Single - phase, ~230V, 50Hz			
Capacity	Cooling	kW	9.0	11.2	12.5	14.0
	Heating		10.0	12.5	14.0	16.0
Input power	W		66	85	131	180
Airflow rate	High	m ³ /h (l/s)	1,630 (452)	1,690 (469)	2,010 (558)	2,270 (629)
	Med		1,370 (379)	1,400 (389)	1,600 (444)	1,780 (493)
	Low		1,140 (316)	1,170 (325)	1,230 (342)	1,280 (355)
Sound pressure level	High	dB (A)	42	45	48	51
	Med		38	38	42	45
	Low		33	34	35	36
Dimensions (H × W × D)	mm		240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700
Weight	kg		46	48	48	48
Connection pipe diameter	Liquid (Flare)	mm	9.52	9.52	9.52	9.52
	Gas (Flare)		15.88	19.05	19.05	19.05
Drain hose diameter (I.D./O.D.)			25 / 32			

Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)



- ① Refrigerant piping flare connection (Liquid)
- ② Refrigerant piping flare connection (Gas)
- ③ Drain piping connection

Wall Mounted


Models (EEV internal)
 ASYA007GTAH **NEW** ASYA009GTAH **NEW**
Models (EEV external)
 ASYE007GTAH **NEW** ASYE009GTAH **NEW**




Features

High efficient compact design

5mm high density heat exchanger is mounted for the first time in the industry.



High density heat exchanger



Making the tube thin:
7 mm → 5 mm

Increase of heat exchanger volume through high density and adopting a sub heat exchanger

6 fan speed control

Multistep airflow control is possible to suit the environment.

Fan speed
Quiet

Low noise
22 dB(A)


- 6 Step Speed
- High
 - Med-H
 - Med
 - Med-L
 - Low
 - Quiet



* Compatible Remote Controller is as follows:
 UTY-RNRY22 / UTY-RSRY / UTY-RHRY / UTY-DCGY / UTY-DTGYZ1 / UTY-ALGXZ1 / UTY-APGXZ1

Easy installation

Communication wiring can be installed easily by opening the front panel and wire cover.



Optimised design


Efficient operation and refrigerant saving are realised by the optimum heat exchanger design suited for small rooms.

Specifications

Model name	ASYA007GTAH		ASYA009GTAH		ASYE007GTAH		ASYE009GTAH	
Power source	Single - phase, ~230V, 50Hz							
Capacity	Cooling	kW	2.2	2.8	2.2	2.8	2.2	2.8
	Heating	kW	2.8	3.2	2.8	3.2	2.8	3.2
Input power	W		19	34	19	34	19	34
	Airflow rate	High	m ³ /h	550	720	550	720	550
Med-H		460		570	460	570	460	570
Med		420		500	420	500	420	500
Med-L		390		410	390	410	390	410
Low		360		360	360	360	360	360
Quiet		330		330	330	330	330	330
Sound pressure level	High	dB (A)	35	43	35	43	35	43
	Med-H		32	38	32	38	32	38
	Med		30	34	30	34	30	34
	Med-L		27	29	27	29	27	29
	Low		24	24	24	24	24	24
	Quiet		22	22	22	22	22	22
Dimensions (H × W × D)	mm	262×820×206	262×820×206	262×820×206	262×820×206	262×820×206	262×820×206	
Weight	kg	7.5	7.5	7.0	7.0	7.0	7.0	
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	6.35	6.35	
	Gas (Flare)		9.52	9.52	9.52	9.52		
Drain hose diameter (I.D./O.D.)	13.8 / 15.8 to 16.7							
EV Kit (option)	-		-		UTR-EV09XB		UTR-EV09XB	

Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.
 When ASY*007GTAH and ASY*009GTAH are connected to a outdoor unit other than the J-III range, gas pipe diameter will require an expander to alter the pipe size from 9.52mm to 12.70mm.

Dimensions (Unit: mm)



Wall Mounted


- Models (EEV internal)**
 ASYA012GCAH **NEW**
 ASYA014GCAH **NEW**
- Models (EEV external)**
 ASYE012GCAH **NEW**
 ASYE014GCAH **NEW**



Features

High efficient and compact design

High efficient and compact design is realised by mounting a high density and large heat exchanger. The compact body makes it possible to install discreetly even in a meeting room or office where comfortable air conditioning is provided.



High density heat exchanger

Making the tube thin: **7 mm → 5 mm**
 Increase of heat exchanger volume due to a high density and adopting sub heat exchanger


Even temperature
 ↓
 Improved heat exchanger effectiveness

Human sensor increases energy saving operation

Energy saving operation starts automatically by detecting the motion of a person in the space. There are 2 modes available, an energy saving mode or a auto off mode available.



Human sensor



6 fan speed control

Multistep airflow control is possible to suit the environment.

Fan speed
Quiet

Low noise
24 dB(A)

6 Step Speed

- High
- Med-H
- Med
- Med-L
- Low
- Quiet



* Compatible Remote Controller is as follows:
 UTY-RNRYZ2 / UTY-RSRY / UTY-RHRY / UTY-DCGY / UTY-DTGYZ1 / UTY-ALGXZ1 / UTY-APGXZ1

Optional parts


- Wired remote controller: UTY-RNRYZ2
 Wireless remote controller: UTY-LNHY
 Simple remote controller: UTY-RSRY, UTY-RHRY

Specifications

Model name		ASYA012GCAH	ASYA014GCAH	ASYE012GCAH	ASYE014GCAH
Power source		Single - phase, ~230V, 50Hz			
Capacity	Cooling	3.6	4.0	3.6	4.0
	Heating	4.0	4.5	4.0	4.5
Input power	W	25	36	25	36
Airflow rate	High	690	800	690	800
	Med-H	610	740	610	740
	Med	560	680	560	680
	Med-L	530	610	530	610
	Low	470	550	470	550
	Quiet	330	330	330	330
Sound pressure level	High	40	44	40	44
	Med-H	37	42	37	42
	Med	35	40	35	40
	Med-L	33	37	33	37
	Low	30	34	30	34
	Quiet	24	24	24	24
Dimensions (H × W × D)	mm	268 × 840 × 203	268 × 840 × 203	268 × 840 × 203	268 × 840 × 203
Weight	kg	8.5	8.5	8.5	8.5
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35
	Gas (Flare)	12.7	12.7	12.7	12.7
Drain hose diameter (I.D./O.D.)		13.8 / 15.8 to 16.7			
EV Kit (option)		-	-	UTR-EV14XB	UTR-EV14XB

Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

Dimensions (Unit: mm)



More comfortable airflow

Comfortable air conditioning is provided by mounting our unique power diffuser.

Heating

Vertical airflow provides powerful floor level heating



Cooling

Horizontal airflow does not blow cool air directly at the occupants in the room.



Wall Mounted

Models

ASYA18GBCH **NEW**

ASYA24GBCH **NEW**

Models

ASYA030GTAH **NEW**

ASYA034GTAH **NEW**



ASYA18 ASYA24



ASYA030 ASYA034




Features

Powerful and comfortable airflow


Powerful airflow

(ASYA030GTAH)



Power diffuser

(ASYA18/24GBCH)




Human sensor (ASYA030/034GTAH only)

A human sensor senses the movement of humans to reduce operation when no one is in the room. The wasteful consumption of energy is reduced automatically to assist in energy usage reduction. (Available to wired remote controller as UTY-RNRYZ2)



Quiet operation and 6 fan speed control

Noise level is drastically reduced through the new airflow structure. Additionally, multistep quiet operation is available by 6 step sound level settings.



- 6-Step Speed**
- High
 - Med-H
 - Med
 - Med-L
 - Low
 - Quiet



* Compatible Remote Controller is as follows:
 UTY-RNRYZ2 / UTY-RSRY / UTY-RHRY / UTY-DCGY / UTY-DTGYZ1 / UTY-ALGXZ1 / UTY-APGXZ1



Specifications

Model name		ASYA18GBCH	ASYA24GBCH	ASYA030GTAH	ASYA034GTAH
Power source		Single - phase, ~230V, 50Hz			
Capacity	Cooling	5.6	7.1	9.0	10.0
	Heating	6.3	8.0	10.0	11.2
Input power	W	32	60	74	103
Airflow rate	High	840	1,100	1,440	1,620 / 1,520
	Med-H	-	-	1,200	1,300
	Med	770	910	1,050	1,120
	Med-L	-	-	940	980
	Low	690	730	890	890
	Quiet	-	-	700	700
Sound pressure level	High	41	48	53	55 / 54
	Med-H	-	-	49	51
	Med	39	43	45	47
	Med-L	-	-	42	43
	Low	35	35	39	39
	Quiet	-	-	33	33
Dimensions (H × W × D)	mm	320 × 998 × 238	320 × 998 × 238	340 × 1,150 × 280	340 × 1,150 × 280
Weight	kg	15	15	18	18
Connection pipe diameter	Liquid (Flare)	6.35	9.52	9.52	9.52
	Gas (Flare)	12.70	15.88	15.88	15.88
Drain hose diameter (I.D./O.D.)		12 / 16		13.8 / 15.8 to 16.7	


Note: Specifications are based on the following conditions.
 Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length: 7.5m; Height difference between outdoor unit and indoor unit: 0m. Voltage: 230V.

When ASYA18GBCH is connected to the outdoor unit other than J-III, pipe diameter should be Ø9.52/Ø15.88 (Liq/Gas).

Dimensions (Unit: mm)

Models: ASYA18 / ASYA24

Models: ASYA030 / ASYA034



- ① Refrigerant piping flare connection (Liquid)
- ② Refrigerant piping flare connection (Gas)
- ③ Drain piping connection

AIRSTAGE™ CONTROL SYSTEMS



User friendly control system provides individual control and centralised control



The AIRSTAGE control system can perform air conditioning control of individual rooms, centralised control by floor or by building, or centralised energy saving air conditioning control for large buildings.

A variety of air conditioning management options are available to match the requirements of the application, including integrating with the building control system, connecting with single split models and the availability of various interfaces.

CONTROL SYSTEM

CONTROL SYSTEM OVERVIEW

INDIVIDUAL CONTROLLER

CENTRALISED CONTROLLER

CONVERTOR / ADAPTOR

OPTIMISED CONTROL SOLUTIONS

Fujitsu General provides a diverse range of flexible control solutions to suit a variety of applications .

SHOP

Type	Individual Control			Centralised Control			Integrating Control (Interface)		
									
	Wired Remote Controller	Central Remote Controller	Wireless Remote Controller	Central Remote Controller	Touch Panel Controller	System Controller	Network Converter for LonWorks®	MODBUS® Convertor	KNX® Convertor
	UTY-RNRYZ2, UTY-RNKYT	UTY-DCGY	UTY-LNHY	UTY-DCGY	UTY-DTGYZ1	UTY-APGXZ1, UTY-ALGXZ1	UTY-VLGX	UTY-VMGX	UTY-VKGX,
Automatic control of A/C (Schedule timer, Weekly timer etc.)	●	●	●	●	●	●			
Customise the level of control for staff and end users (RC Prohibition, Room temp set point limitation etc.)		●	●	●	●	●	●	●	●
Group control		●	●	●	●	●			
Advanced energy saving (Peak cut, Indoor unit rotation operation etc.)						●			
Remote management				●	●	●			
Manage multiple sites				●	●	●			
Monitor energy consumption						●			
Control third party products						●			
Integrate FGL A/C into BMS							●	●	●

HOTEL

Type	Individual Control			Centralised Control			Integrating Control (Interface)				
											
	Wired Remote Controller	Simple Remote Controller	Wireless Remote Controller	Central Remote Controller	Touch Panel Controller	System Controller	BACnet® Gateway	Network Converter for LonWorks®	MODBUS® Convertor	KNX® Convertor	External Switch Controller
	UTY-RNRYZ2, UTY-RNKYT	UTY-RSRY, UTY-RHRY	UTY-LNHY	UTY-DCGY	UTY-DTGYZ1	UTY-APGXZ1, UTY-ALGXZ1	UTY-ABGXZ1, UTY-VBGX	UTY-VLGX	UTY-VMGX	UTY-VKGX	UTY-TEKX
Local control for hotel guest	●	●	●								
Centralised A/C control for common space				●	●	●	●	●	●	●	
Limited control for hotel guests				●	●	●	●	●	●	●	
Remote management					●	●					
Advanced energy saving (Peak cut, Indoor unit rotation operation etc.)						●	●				
Monitor energy consumption						●					
Control third party products						●					
Integrate FGL A/C into BMS							●	●	●	●	
Interlock with window contact											●
Interlock with key-card											●

OFFICE

Type	Individual Control			Centralised Control			Integrating Control (Interface)				
											
	Wired Remote Controller	Simple Remote Controller	Wireless Remote Controller	Central Remote Controller	Touch Panel Controller	System Controller	BACnet® Gateway	Network Converter for LonWorks®	MODBUS® Convertor	KNX® Convertor	External Switch Controller
	UTY-RNRYZ2, UTY-RNKYT	UTY-RSRY, UTY-RHRY	UTY-LNHY	UTY-DCGY	UTY-DTGYZ1	UTY-APGXZ1, UTY-ALGXZ1	UTY-ABGXZ1, UTY-VBGX	UTY-VLGX	UTY-VMGX	UTY-VKGX	UTY-TEKX
Local control for office staff	●	●	●	●							
Automatic control of A/C (Schedule timer, Weekly timer etc.)	●		●	●	●	●	●				
Centralised A/C control for management				●	●	●	●	●	●	●	
Customise the level of control for office staff (RC Prohibition, Room temp set point limitation etc.)				●	●	●	●	●	●	●	
Advanced energy saving (Peak cut, Indoor unit rotation operation etc.)						●	●				
Remote management					●	●					
Energy charge apportionment					●	●	●*				
Monitor energy consumption						●					
Control third party products						●					
Integrate FGL A/C into BMS							●	●	●	●	
Interlock with door contact											●
Interlock with human sensor for meeting room											●

* UTY-ABGXZ1 only

CONTROL SYSTEM OVERVIEW

User's needs are supported by offering a variety of controls, such as individual control, central control and building management control options.

For Light Commercial
• Small VRF



For Commercial
• Large VRF



Air Conditioning Individual Control



Wired Remote Controller (Touch panel)
UTY-RNRYZ2



Wired Remote Controller
UTY-RNKYT



Simple Remote Controller
UTY-RSRY
UTY-RHRY
Without operation mode




Wireless Remote Controller
UTY-LNHY



IR Receiver Unit
UTB-YWC For ducted type
UTY-LRHYB1 For cassette type

For ducted For cassette

Air Conditioning Centralised Control



System Controller (Software)
UTY-APGXZ1 / UTY-ALGXZ1 (Lite edition)

Max. controllable
1600*
Indoor units

* Lite edition max. controllable 400 indoor units



Touch Panel Controller
UTY-DTGYZ1

Max. controllable
400
Indoor units



Central Remote Controller
UTY-DCGY

Max. controllable
100
Indoor units

Converter / Adaptor For external device

BACnet® Gateway
UTY-ABGXZ1 (Software)



NEW BACnet® Gateway
UTY-VBGX (Hardware)




Network Converter (BMS/LonWorks®)
UTY-VLGX



MODBUS® Converter
UTY-VMGX



KNX® Converter For VRF
UTY-VKGX



External Switch Controller
UTY-TEKX




Card-key
(Field supplied)

BMS/BAS *2




BMS, Home automation system




*1. USB Adaptor: Echelon® U10 USB Network Interface
*2. BMS/BAS: Building Management System/Building Automation System

Converter / Adaptor For system expansion


Network Converter (DC power supply)
UTY-VTGX



Network Converter
UTY-VGGXZ1



Signal Amplifier
UTY-VSGXZ1



COMPARISON TABLE OF CONTROLLERS

Type										
	Wired Remote Controller (Touch panel)	Wired Remote Controller	Simple Remote Controller	Simple Remote Controller *1	Wireless Remote Controller	Central Remote Controller	Touch Panel Controller	System Controller Lite <small>Software</small>	System Controller <small>Software</small>	
Model name	UTY-RNRYZ2	UTY-RNKYT	UTY-RSRY	UTY-RHRY	UTY-LNHY	UTY-DCGY	UTY-DTGYZ1	UTY-ALGXZ1	UTY-APGXZ1	
Max. controllable remote controller groups	1	1	1	1	1	100	400	400	1600	
Max. controllable indoor units	16	16	16	16	16	100	400	400	1600	
Max. controllable groups	-	-	-	-	-	16	400	400	1600	
Air conditioning control function	On / off	●	●	●	●	●	●	●	●	
	Operation mode setting	●	●	●	-	●	●	●	●	
	Fan speed setting	●	●	●	●	●	●	●	●	
	Room temp. setting	●	●	●	●	●	●	●	●	
	Room temp. set point limitation	●	-	●	●	-	●	●	●	
	Test operation	●	●	●	●	●	●	-	-	
	Up / down air direction flap setting	●	●	●	●	●	●	●	●	
	Right / left air direction flap setting	●	●	-	-	●	●	●	●	
	Individual louver control	●	-	-	-	-	-	●	-	
	Group setting	-	-	-	-	-	●	●	●	
	RC prohibition	-	-	-	-	-	●	●	●	
	Anti freeze setting	●	-	-	-	-	●	●	●	
	Set temp. auto return	●	-	-	-	-	-	●	-	
	Economy mode setting	●	●	-	-	●	●	●	●	
	Human sensor control	●	-	-	-	-	-	●	●	
	Custom auto setting	●	-	-	-	-	-	●	-	
Display	Error	●	●	●	-	●	●	●	●	
	Defrosting	●	●	●	●	-	●	●	●	
	Current time	●	●	-	-	●	●	●	●	
	Day of week	●	●	-	-	-	●	●	●	
	R.C. prohibition	●	●	●	●	-	●	●	●	
	Cooling / heating priority	●	●	●	●	-	●	●	●	
	Address display	●	●	●	●	-	●	●	●	
	Room temp	●	-	●	●	-	●	-	-	
	Multi language	●	-	-	-	-	●	●	●	
	Summer time	●	-	-	-	-	●	●	●	
	Name registration	●	-	-	-	-	●	●	●	
	Backlight	●	-	●	●	-	●	●	-	
	2D floor layout / 3D building display	-	-	-	-	-	-	-	-	●
Timer	Schedule timer	Period	Week	Week	-	-	Week	Year	Year	Year
		On/off, Temp, Mode, Times per day	8	4	-	-	20	20	144	144
	On / off timer	●	●	-	-	●	-	-	-	
	Sleep timer	-	-	-	-	●	-	-	-	
	Program timer	-	-	-	-	●	-	-	-	
	Auto off timer	●	-	-	-	-	-	●	-	
Day off	●	●	-	-	-	●	●	●		
Min. unit of timer setting (Minutes)	10 + 30	30	-	-	5	10	10	10	10	
Control	Status monitoring system	-	-	-	-	●	●	●	●	
	Electricity charge apportionment	-	-	-	-	-	○	○	●	
	Error history	●	●	-	-	-	●	●	●	
	Emergency stop	-	-	-	-	-	●*2	●*2	-	
	Remote management	-	-	-	-	-	●	○	●	
	Energy saving management	-	-	-	-	-	-	○	○	
	E-mail notification for malfunction	-	-	-	-	-	●	●	●	
	Key lock	● Child lock	-	-	-	-	● Password setting	● Password setting	● Password setting	● Password setting
Low noise mode	-	-	-	-	-	●	-	-		

*1 "Operation mode" setting is not available for this model. *2 This function is available only through external input control. ●: Supported ○: Optional function -: Not supported yet

Wired Remote Controller (Touch Panel)

UTY-RNRYZ2

Easy operation with a high-definition large LCD touch panel screen

- Easy touch operation via the touch screen LCD panel
- Built-in weekly / daily timer (ON / OFF, Temp, Mode)
- Backlight enables easy operation in a darkened room
- Room temperature display
- Control up to 16 indoor units
- 12 different language settings (English, Chinese, French, German, Spanish, Russian, Polish, Italian, Greek, Portuguese, Turkish and Dutch)
- 2-wire type

Max. controllable
16
indoor units



Functions


High performance and compact size

- In addition to the individual control, various energy saving controls can be utilised via the controller.



Accurate and comfortable control

- Indoor temperature can be detected accurately by the inclusion of a thermo sensor in the body of the wired controller.



Room temperature sensor

Room temperature display

Backlight


- Backlight enables easy operation in a darkened room.
- The backlight setting can be adjusted for 30 or 60 seconds.
- Backlight activates whilst the controller is in use and turns off 30 or 60 seconds after user operation stops.



Various convenient functions


Displays setting status and limitations

- The remote controller settings can be easily checked



Summer time display

- This function can be set easily from the Menu screen



Child lock

- Lock / unlock method: Push the ON / OFF button and the screen (4 seconds)



Name registration

- Remote controller names can be registered in the remote controller screen. This makes it easy to identify the indoor unit you want to control in the room




Various energy saving controls

Custom Auto


- Maintains 2 separate set points for heating and cooling
 - Automatically changes mode between heating and cooling
- * This function is not available for some models.

Cooling set temp. 27°C, Heating set temp. 26°C



Auto OFF timer

- The indoor unit is automatically turned off when it reaches the preset operating time frame
- The time frame of the "Auto off timer" allows flexibility for setting and scheduling
- Can be set off time 30 to 240 minutes



Ex.) a particular interval time hour (17:00 to 24:00) to prevent forgetting to turn off
Set off time: 1 hour

2 schedules weekly timer

- 2 schedules, for example summer and winter can be set
- 8 setting changeable per day of week (Setting items: On / Off, Temperature, Mode, Time)



Set temperature auto return

- The setting temperature automatically returns to the previous temperatures setting
- The time range in which the set temperature can be changed is 10 to 120 minutes

Set temperature upper and lower limit settings

- The set temperature range can be set for each operation mode. (Cooling / Heating / Auto)

Specifications


Model name	UTY-RNRYZ2	
Power supply	DC 12V	
Dimensions (H x W x D)	120 x 120 x 20.4	
Weight	220	

DC12V is supplied by indoor unit.

Simplified installation


Uses non polar 2 wire type

- Incorrect wiring can be prevented by using non-polar 2-wire



Auto address setting / setting position notification

- Reduces errors and install time compared with the current specification of using the Rotary SW
- When using the touch panel controller to control a remote controller group, new functionality enables the controller to set the respective RC addresses
- After the addresses are assigned these can be confirmed from the indoor unit



Easy maintenance

Error history display

- Errors that occur in the indoor unit or on the remote controller are saved in the error history
- A maximum of 32 error incidents can be saved



Wired Remote Controller

Max. controllable
16
indoor units

UTY-RNKYT

The room temperature can be controlled by detecting the temperature from the built-in sensor

- Simple operation with built-in weekly / daily timer
- Control up to 16 indoor units
- Up to 2 wired remote controllers can be connected to a single indoor unit



Functions



Powerful features and compact size

This wired remote controller incorporates four primary functions into a single unit.



Accurate and comfortable

Indoor temperature can be detected by the inclusion of a thermo sensor within the body of the wired controller. This wired remote controller and the optional remote sensor allows flexibility in sensor location, suitable for a variety of applications.



Displayed temperature is set temperature.

Specifications

Model name	UTY-RNKYT	
Power supply	DC 12V	
Dimensions (H x W x D)	mm	120 x 120 x 18
Weight	g	160

DC12V is supplied by indoor unit.

Simple Remote Controller

Max. controllable
16
indoor units

UTY-RSRY

UTY-RHRY (Without operation mode)

Compact remote controller provides access to basic functions

- Up to 16 indoor units can be controlled with one remote controller
- Suitable for hotels or offices as it is easily operated with no complex functions
- Stylish design: Simple design to match the stylish interior
- Large LCD screen and simple operation buttons
- Backlight: White colored backlight on monitor enables easy operation in dark environments
- 2-wire type



UTY-RSRY
UTY-RHRY
Without operation mode

Functions

Corresponding with various applications


Vertical louver control:

Vertical air flow direction can be adjusted for Mini Duct & Slim Duct types using the auto louver option and also cassette types, to suit indoor units installed in applications such as hotels and conference rooms.




Room temperature set point limitation:

The Simple Remote Controller can assist with management of energy usage in small buildings without the central control unit.



Built in room temperature sensor:

The Simple Remote Controller detects actual room temperature and controls room climate accordingly.



Specifications

Model name	UTY-RSRY		UTY-RHRY	
Power supply	DC 12V			
Dimensions (H x W x D)	mm	120 x 75 x 19.4		
Weight	g	120		

DC12V is supplied by indoor unit.

Wireless Remote Controller

UTY-LNHY

Simple and sophisticated operations with a choice of 4 daily timers

- A single controller controls up to 16 indoor units

Max. controllable
16
indoor units

Selectable
4
daily timers





Functions

Built-in daily timer

Select from 4 different timer programs: ON / OFF / Program / Sleep

Program timer: The program timer operates the ON and OFF timer once within a 24 hour period.

Sleep timer: The sleep timer function automatically corrects the set temperature according to the time setting to prevent excessive cooling or heating during sleep hours.




Specifications

Model name	UTY-LNHY	
Power supply	1.5V (R03 / LR03 / AAA) × 2	
Dimensions (H x W x D)	mm	170 × 56 × 19
Weight	g	85

Easy operation with multiple indoor units

The code selector switch prevents indoor unit from unintended control. (Up to 4 codes can be set.)




Wide and precise



Address setting

During installation work, address setting can be performed using the wireless remote controller, thus eliminating manual switch setting.



IR Receiver Unit

UTB-TWC

Option required to control ducted type units* via a Wireless Remote Controller


*Only the Large Airflow Duct cannot be connected to the IR Receiver Unit.

- Up to 16 indoor units can be controlled with one remote controller
- Suitable for hotels or offices as it is easily operated with no complex functions



Functions

Wiring connection



Specifications

Model name	UTB-TWC	
Power supply	DC 5V	
Dimensions (H x W x D)	mm	145 × 90 × 30
Weight	g	150


IR Receiver Unit

UTY-LRHYB1

Cassette type indoor units can be controlled with the Wireless Remote Controller



Functions



Specifications

Model name	UTY-LRHYB1	
Power supply	DC 5V	
Dimensions (H x W x D)	mm	193.9 × 193.9 × 31.2
Weight	g	140

Central Remote Controller

Max. controllable
100
indoor units

Max. controllable
16
groups

UTY-DCGY

Central control of small and medium sized buildings and tenancies. The operation status of all connected indoor units can be viewed easily on a large LCD monitor to simplify individual control to batched control.




- Individual control and monitor of 100 indoor units
- 5 inch TFT colour screen
- User friendly view and easy operation
- External input / output contact
- Detachable power supply unit
- 7 different language settings available (English, Chinese, French, German, Spanish, Russian, Polish)

Functions

System overview

- Allows multiple indoor units to be grouped (Max.16 groups controlled)
- Interlock with external devices



Functions


- Diverse control of indoor units
- Remote controller prohibition (All, ON / OFF, Mode, Temp, Timer, Filter)
- Weekly timer
- Error history
- Automatic clock adjustment




Easy installation

- The control panel and power supply unit can be installed separately
- For flexibility in installation, the control can be installed in a separate or integrated fashion


Setting pattern 1



Setting pattern 2



- Automatic or manual indoor unit registration



Specifications

Model name		UTY-DCGY	
		Control Panel	Power Supply Unit
Power supply		DC 5 V	100-240V, 50-60Hz, Single phase
Dimensions (H x W x D)	mm	120 x 162 x 25.7	99 x 135 x 39.2
Weight	g	308	355



Touch Panel Controller

UTY-DTGYZ1

- Large-sized 7.5 inch TFT colour
- LCD easy touch operation
- Stylish shape and design to suit all applications
- Up to 400 indoor units can be controlled
- Selectable 2 display types (Icon / List) in monitoring mode
- Supports 7 different languages - English, Chinese, French, German, Spanish, Russian, Polish
- Mounted with LAN interface for remote control and operation, external input / output with emergency stop and batch ON / OFF


Max. controllable 400 indoor units	Max. controllable 100 outdoor units	Max. controllable 400 groups
---	--	---



Functions


Control and monitoring from anywhere

- Control and monitor Fujitsu air conditioners via LAN or Internet
- Allow user or tenants to manage assigned equipment by their PC or tablet from anywhere
- Error messages can be notified automatically by email upon an error occurrence to allow the issue to be handled promptly.



Control and monitoring from anywhere

- Control and monitor Fujitsu air conditioners via LAN or Internet
- Allow the user or tenant to manage only assigned equipment by their PC or tablet from anywhere
- Error messages can be notified automatically by email upon an error occurrence to enable the issue to be handled promptly



Easy maintenance

- Flat touch screen is easily cleaned
- Non glare coating on touch panel controller minimises fingerprint marking
- Easy to remove front cover





Easy installation

- The touch panel controller is easily mounted to the wall
- The flat back surface allows the controller to be installed wherever required
- No additional components are required for installation



Up to 400 indoor units can be controlled



Not only operations but also detail settings such as schedule or group settings can be operated from remote locations.

Smart Phone


Model name	Browser
Nexus 6P (Android 7.1.1)	Google Chrome 5.5
iphone7 (iOS 10.1)	Safari 10

Tablet

Model name	Browser
ipad Pro 9.7inch (iOS 10.2.1)	Safari 10


Flexible access permissions with individual user levels

The administrator can register multiple users to permit which indoor unit(s) and which functions can accessed.



Additional language functionality

Available in 7 different languages - English, Chinese, French, German, Spanish, Russian and Polish as standard. Additional languages can be integrated on a remote device by creating a language database. Additional languages are displayed only on the remote device. The touch panel controller cannot be configured to display these additional languages.




Functions

Electricity charge apportionment

Option UTY-PTGXA

- Electricity charge apportionment can be utilised to easily attribute power usage to each tenant based on their usage

- Apportionment charge / bill calculation
- Tenant (block) setting
- Common facilities apportionment setting
- Rated power consumption allotment setting
- Individual calculation for both cooling and heating
- Electricity meter supported



*: Electricity meter (1 unit) can be connected to external input connector of the TPC unit. In this case, electricity meter cannot be connected to outdoor unit simultaneously.


Automatic summer time setting

Function overview

- 1) This function enables a schedule to be set within the system to adjust the timer to summer time at the appropriate time to ensure the time matches the time zone.


Automatic clock adjustment

- 2) The time setting of each controller can be set from the one location.




Outdoor low noise operation

Users can choose from 4 low noise levels, depending on the installation environment. The operation time can be set using the timer.



Quiet priority setting




Energy saving control

Custom Auto

- Maintains 2 separate set points for heating and cooling
- Automatically changes mode between heating and cooling

* This function is not available for some models.

Cooling set temp. 27°C, Heating set temp. 26°C



FUNCTIONS SUMMARY

	UTY-DTGYZ1	Monitoring side
Air conditioning control function		
On / Off	●	●
Operation mode setting	●	●
Fan speed setting	●	●
Room temp. setting	●	●
Room temp. set point limitation	●	●
Test operation	●	●
Up/down air direction flap setting	●	●
Right/left air direction flap setting	●	●
Individual louver control	●*1	●
Group setting	●	●
RC prohibition	●	●
Anti freeze setting	●	●
Set temp. auto return	-	●
Various energy saving controls	-	●
Economy mode setting	●	●
Human sensor control	-	●
Custom auto setting	●	●
Display		
Error	●	●
Defrosting	●	●
Current time	●	●
Day of week	●	●
R.C. prohibition	●	●
Cooling/heating priority	●	●
Address display	●	●
Room temp	●	●
Multi language	●	●
Summer time	●	●
Time zone setting	●	●
Name registration	●	●
Backlight	●	●
Language setting	7	7+other

●: Supported ○: Optional function - : Not supported yet

*1 Only setting cancellation can be operated.

*2 This function is available only through external input control.

	UTY-DTGYZ1	Monitoring side
Timer		
Schedule timer	Period	Year
	On/off, Temp, Mode, Times per day	20
On/off timer	-	-
Sleep timer	-	-
Program timer	-	-
Auto off timer	-	●
Day off	●	●
Min. unit of timer setting (Minutes)	10	10
Control		
Status monitoring system	●	●
Electricity charge apportionment	○	○
Error history	●	●
Emergency stop	●*2	●*2
Remote management	-	●
Energy saving management	-	-
Email notification for malfunction	-	●
Key lock	● Password setting	-
Low noise mode	●	●

Specifications

Model name		UTY-DTGYZ1
Power supply		100-240V 50/60Hz, Single phase
Dimensions (H x W x D)	mm	260 x 246 x 54
Weight	g	2,150
Interface		Transmission / LAN / USB / EXT IN / EXT OUT / Reset SW

System Controller Software

UTY-APGXZ1

System Controller offers the advanced integrated monitoring and control of the VRF network system from small to large scale buildings.

- Up to a maximum of 4 VRF network systems, 1600 indoor units, and 400 outdoor units can be controlled
- In addition to the air conditioning control function, central remote control, electricity charge calculation, schedule management and energy saving functions ensure the building manager and owner needs are met

Max. controllable VRF network systems	Max. controllable indoor units	Max. controllable outdoor units
4	1,600	400



Max. controllable VRF network system	Max. controllable indoor units	Max. controllable outdoor units
1	400	100



System Controller Lite Software

UTY-ALGXZ1

System Controller Lite has functions suited for air conditioning management in small and medium scale buildings.

- Up to a maximum of 1 VRF network system, 400 indoor units, and 100 outdoor units can be controlled
- In addition to air conditioning precision control function, a variety of management software is available as an option to give customers a wide range of choice

Functions

User friendly view and operation

- **Click and Operate:** The property is shown visually from the perspective most suitable for operation and operated accordingly (Click and Operate). You can select from among the 4 displays of site, building, floor, or list.
- **Define custom groups for batched control:** Indoor units can be grouped for simple batched control from a tree menu. Grouping by hierarchal structure, such as by section, division or department is possible.

Click & Operate the whole building! Properties can be shown using one of the four displays of site, building, floor, or list.

Click & Operate any specified unit(s)!

The display is easily changed by pressing the button.

Batched control of freely defined groups

Batched control of freely selected units

Click & Operate the whole floor!

Click & Operate the unit!


The floor layout drawing can be imported to easily make the settings for the actual building.

Note: 2D floor layout / 3D building display are not available for System Controller Lite.

3rd party devices connected by Modbus can be controlled

Standard for System Controller Option for System Controller Lite UTY-PLGXX2

When a Modbus Adaptor (locally purchased) is connected to PC, the devices supported by Modbus can be controlled from a central location. Electricity usage can be reduced by enabling all unrequired devices to be turned off or scheduled to turn off at the end of the day.



Diverse operation management and data management

Schedule management

- Annual schedules can be set for each remote controller group / user defined group
- Start / stop, operating mode, remote controller prohibition, and temperature settings can be set up to 143 times per day at 10 minute intervals for up to 101 configurations for each remote controller group
- Allows programming of special settings for holidays, including public holidays, for a complete year
- Low noise operation of the outdoor unit can be scheduled



Diverse control of indoor and outdoor unit

- Indoor unit operation state, operation mode, etc. are displayed
- Indoor unit start / stop and operation mode switching
- Room temperature set point limitation

Error display and email notification

Errors are notified with a popup message, audible sound and email real time when the error occurs. Errors for the past year are logged and can be reviewed at anytime.

Remote controller prohibition

This prohibits changes to the operation mode, temperature, start/stop etc.

Data base import/export

Imports / exports registration data, layout data, and image data. Only the administrator can make this setting.

Automatic clock adjustment


The time setting for each controller can be set centrally with one command.

Operating and control record

Displays the history of operation status and control.

Web Operation

PC and smartphones can be used as a simple remote controller.



Functions

Electricity charge apportionments[^]


Electricity charge apportionment calculation framework

Suppose you want to find the power consumed by the air conditioners of each tenant from the electricity charge for each month. With the electricity charge apportionment function, the used energy apportionment ratio will be provided, calculating in detail the energy consumed by the units within each tenancy. This information is then used to calculate the charges for the electricity consumed for air conditioning by each tenant from the total electricity charges in the bill from the electric power company. (See figure on the right)

The detailed calculation takes into consideration variables such as unused rooms and nighttime electricity charges and shows them in the charge calculation sheet.

Standard for System Controller **Option** for System Controller Lite UTY-PLGXA2


System Configuration Example



Remote management

The System Controller may be used on site or remotely over various networks for remote central control. System Controller requires 2 software applications working together. VRF Controller runs on site and communicates with the VRF system. VRF Explorer runs remotely and provides user interface and communicates with the VRF Controller. VRF Controller and the VRF Explorer program may operate on a single PC or on different PCs separated by a network. By using VRF Explorer software, one PC can perform central control of 10 VRF system sites with a max. 20 buildings per site.


Standard for System Controller **Option** for System Controller Lite UTY-PLGXA2



Energy saving management


Option for System Controller UTY-PEGXZ1 **Option** for System Controller Lite UTY-PLGXE2

A variety of energy saving operations can be set and managed depending on the season, weather, and time period.




Peak cut operation

A power meter is connected to detect the total power consumption by shifting the indoor unit set temperature, set the indoor unit forced thermostat off, and taking other measures to carefully control the power consumed to maintain target power consumption set for the specified time. The indoor units to be controlled can be grouped and the control level can be set.




Indoor unit rotation operation

The operation of indoor units can be automatically rotated within a group in accordance with the set annual schedule to reduce power consumption while maintaining comfort. The indoor unit operation stop rate can be selected.



Outdoor unit capacity save

Outdoor unit capacity save function switches the outdoor unit capability upper limit to suppress power consumption during hot summers and cold winters by averaging the power saving effect of each refrigerant system. You can select from 50% or more of the capacity upper limit.



FUNCTIONS SUMMARY

Function	Type	System Controller			System Controller Lite				
		UTY-APGXZ1	Option UTY-PEGXZ1	UTY-ALGXZ1	Option UTY-PLGXR2	Option UTY-PLGXA2	Option UTY-PLGXE2	Option UTY-PLGXX2	
System specifications	Max. VRF networks supported	4	—	1	—	—	—	—	
	Max. indoor unit / remote controller groups per VRF network	400	—	400	—	—	—	—	
	Max. outdoor units per System controller	100	—	100	—	—	—	—	
	Max. indoor units / remote controller groups per System controller	1600	—	400	—	—	—	—	
	Max. outdoor units per System controller	400	—	100	—	—	—	—	
Site supervision	Multi site display	10	—	10	—	—	—	—	
	Number of building / 1 site	20	—	—	—	—	—	—	
	Number of floor per 1 site	200	—	—	—	—	—	—	
	Number of floor per 1 building	50	—	—	—	—	—	—	
	3D graphical layout view	●	—	—	—	—	—	—	
	2D graphical layout view	●	—	—	—	—	—	—	
Error management	List display	●	—	—	—	—	—	—	
	Tree display	●	—	—	—	—	—	—	
	Group display	●	—	—	—	—	—	—	
	Error notification	●	—	—	—	—	—	—	
	Audible alarm	●	—	—	—	—	—	—	
History	Error email notification	●	—	—	—	—	—	—	
	Error history	●	—	—	—	—	—	—	
Operation control	Operation history	●	—	—	—	—	—	—	
	Control history	●	—	—	—	—	—	—	
	Individual control	On/Off	●	—	—	—	—	—	—
		Operation mode	●	—	—	—	—	—	—
		Room temperature	●	—	—	—	—	—	—
		Fan speed	●	—	—	—	—	—	—
		Air flow direction	●	—	—	—	—	—	—
		Economy mode	●	—	—	—	—	—	—
		Room temperature set point limitation	●	—	—	—	—	—	—
		Test operation	●	—	—	—	—	—	—
		Antifreeze	●	—	—	—	—	—	—
		Outdoor unit low noise setting	●	—	—	—	—	—	—
	Individual management	Remote control prohibition setting	●	—	—	—	—	—	—
		Temperature upper and lower limit setting	●	—	—	—	—	—	—
		Filter sign reset	●	—	—	—	—	—	—
Other	Memory operation	●	—	—	—	—	—	—	
	Pattern operation	●	—	—	—	—	—	—	
Schedule	Web operation	●	—	—	—	—	—	—	
	Annual schedule	●	—	—	—	—	—	—	
	Special day setting	●	—	—	—	—	—	—	
	On / off per day	72	—	72	—	—	—	—	
	On / off per week	504	—	504	—	—	—	—	
Remote management	Day off	●	—	—	—	—	—	—	
	Min. unit of timer setting (Minutes)	10	—	10	—	—	—	—	
	Low noise mode weekly schedule	●	—	—	—	—	—	—	
	Remote monitoring	●	—	—	—	—	—	—	
	Remote operation control	●	—	—	—	—	—	—	
	Remote function setting	●	—	—	—	—	—	—	
	Web remote controller	●	—	—	—	—	—	—	
	Apportionment charge/bill calculation	●	—	—	—	—	—	—	
	Tenant (block) setting	●	—	—	—	—	—	—	
	Common facilities apportionment setting	●	—	—	—	—	—	—	
Electricity charge apportionment	Rated power consumption allotment setting	●	—	—	—	—	—	—	
	Individual calculation at cooling and heating	●	—	—	—	—	—	—	
	Electricity meter supported	●	—	—	—	—	—	—	
	Indoor unit rotation	●	—	—	—	—	—	—	
	Peak cut control	●	—	—	—	—	—	—	
Energy saving management	Outdoor unit capacity save	●	—	—	—	—	—	—	
	Record of energy saving operation	●	—	—	—	—	—	—	
	Energy saving information	●	—	—	—	—	—	—	
	Power consumption monitor	●	—	—	—	—	—	—	
	Electricity meter supported	●	—	—	—	—	—	—	
External Device Control	Monitor	●	—	—	—	—	—	—	
	Control	●	—	—	—	—	—	—	
Others	Database import/export	●	—	—	—	—	—	—	
	Automatic clock adjustment	●	—	—	—	—	—	—	
	Multi language	7 languages	—	7 languages	—	—	—		

●●: Available. --: Not available. *: Power calculation application software is necessary, please contact the local FGL representative.

Personal computer system requirements

The required PC specifications are shown in the following table.

	System Controller	System Controller Lite
Operating system	<ul style="list-style-type: none"> Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1 Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit) Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit) [Supported languages] English, Chinese, French, German, Russian, Spanish, and Polish	<ul style="list-style-type: none"> Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1 Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit) Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit) [Supported languages] English, Chinese, French, German, Russian, Spanish, and Polish
CPU	Intel® Core™ i3 2 GHz or higher	Intel® Core™ i3 2 GHz or higher
Memory	• 2 GB or more (for Windows® 7 [32-bit])	• 4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)
HDD	40 GB or more of free space	35 GB or more of free space
Display	1024 x 768 or higher resolution	1024 x 768 or higher resolution
Interface	<ul style="list-style-type: none"> Ethernet port (for getting access to the Internet using LAN) or Modem (for getting access to the Internet using Public Telephone Line) USB ports (Maximum of 6 ports) (Required only for the Server PC that works as VRF Controller) Maximum of 2 USB ports are required for WHITE-USB-KEY/WibuKey connection Maximum of 4 USB ports are required for Echelon® U10 USB Network Interface * Maximum number of required USB port depends on the applicable system configuration. 	<ul style="list-style-type: none"> Ethernet port (for getting access to the Internet using LAN) or Modem (for getting access to the Internet using Public Telephone Line) USB ports (Maximum of 6 ports) (Required only for the Server PC that works as VRF Controller) Maximum of 4 USB ports are required for WHITE-USB-KEY/WibuKey connection 1 USB port is required for Echelon® U10 USB Network Interface * The maximum number of required USB port depends on the applicable system configuration.
Graphic accelerator	Microsoft® DirectX® 9.0c compatible	Microsoft® DirectX® 9.0c compatible
Software	Adobe® Reader® 9.0 or later	Adobe® Reader® 9.0 or later

• Echelon® U10 USB Network Interface - TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)re.

Type	For System Controller			For System Controller Lite			
	System controller	Option Energy manager	System Controller Lite	Remote access	Option Electricity charge apportionment	Option Energy saving	Option Central Control
Model name	UTY-APGXZ1	UTY-PEGXZ1	UTY-ALGXZ1	UTY-PLGXR2	UTY-PLGXA2	UTY-PLGXE2	UTY-PLGXX2
WHITE-USB-KEY	1	1	1	1	1	1	1

*1: Software protection key to be inserted in a USB slot running System Controller or System Controller Lite.

System Controller or System Controller Lite may only run on a PC with WHITE-USB-KEY. However, WHITE-USB-KEY is not required for remote VRF Explorer software.

^ The electricity charge apportionment function does not calculate official electricity charges like those established by the laws and regulations of each country.

BACnet® Gateway

Max. controllable VRF network systems	Max. controllable indoor units	Max. controllable outdoor units
4	1,600	400

UTY-ABGXZ1

- Enables the connection of medium to large sized BMS to VRF network system via BACnet®, a global standard for open networks
- A maximum of 1600 indoor units with 4 VRF network systems (a maximum of 400 indoor units and 100 outdoor units for one network system) can be connected to one BACnet® Gateway
- Control or monitor VRF network system from BMS via BACnet® Gateway
- Compatible with BACnet® (ANSI / ASHRAE-135-2012) application specific controller (B-ASC).
- Compatible with BACnet®/IP over Ethernet
- Scheduling, alarm and event functions as well as Electricity Change Apportionment function are provided in the BACnet® Gateway
- The connection between VRF network system to personal computer is possible via small U10 USB interface. However, both U10 USB interface and personal computer are field supplied items
- Available for use in 7 different languages, English, Chinese, French, German, Spanish, Russian, Polish




WHITE-USB-KEY (Software Protection Key)



BTL is a registered trademark of BTL. BTL does not warrant, agree or hold products for sale with BTL. BTL is not responsible for the BTL. BTL is a registered trademark of the BTL. BTL is a registered trademark of the BTL.

Functions

Installation example



Personal computer system requirements

	UTY-ABGXZ1
Operating system	<ul style="list-style-type: none"> • Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit) • Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit) [Supported languages] English, Chinese, French, German, Russian, Spanish, and Polish
CPU	Intel® Core™ i3 2 GHz or higher
Memory	<ul style="list-style-type: none"> • 2 GB or more (for Windows® 7 [32-bit]) • 4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)
HDD	40 GB or more of free space
Display	1024 x 768 or higher resolution
Interface	<ul style="list-style-type: none"> • Ethernet port (for getting access to the Internet using LAN) • USB ports (Maximum of 5 ports) - 1 USB port is required for WHITE-USB-KEY/WibuKey connection - Maximum of 4 USB ports are required for Echelon® U10 USB Network Interface * Maximum number of required USB ports depends on the applicable system configurations.
Software	Adobe® Reader® 9.0 or later
	• Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

Name and shape	Quantity	Application
WHITE-USB-KEY	1	Includes the software and manuals, license for BACnet® Gateway.

BACnet® Gateway (Hardware)

Max. controllable VRF network system	Max. controllable refrigerant system	Max. controllable indoor units
1	32	128


NEW UTY-VBGX

- BACnet® Gateway enables connection between the BMS and FG VRF system
- A maximum of 128 indoor units and 32 refrigerant system can be connected to a single BACnet® Gateway
- Compatible with BACnet® (ANSI / ASHRAE-135-2010) application specific controller (B-ASC)
- Compatible with BACnet®/IP over Ethernet



Functions

Installation example



Specifications

Model name	UTY-VBGX
Number of controllable indoor units	128
Number of controllable refrigerant system	32
Number of controllable VRF network	1
Number of connectable units / one VRF network	4


Model name	UTY-VBGX
Power supply	208-240V 50/60Hz, single phase
Power consumption	W -
Dimensions (H x W x D)	mm 260 x 59 x 145
Weight	g -

Network Converter for LONWORKS®

Max. controllable Units to BMS	Max. controllable indoor units	Max. controllable outdoor units
4	128	100


UTY-VLGX

- For connection between VRF network system and a LONWORKS® open network for management of small to medium sized BMS and VRF network systems
- The UTY-VLGX permits central monitoring and control of a VRF network system from a BMS through a LONWORKS® interface
- Up to 128 indoor units can be connected to one Network Converter for LONWORKS®



Functions

Installation example



Specifications

Model name	UTY-VLGX
Power supply	208-240V 50/60Hz, Single phase
Power consumption	W 4.5
Dimensions (H x W x D)	mm 67 x 288 x 211
Weight	g 1,500

Transmission specifications (BMS side)

Transmission speed	78 kbps
Transceiver	FT-X1 (Echelon® Corporation)
Transmission way form	Free topology
Terminal resistor	None (It attaches at the terminal of a network.)


MODBUS® Convertor

UTY-VMGX

The MODBUS Convertor allows a complete integration of air conditioners into MODBUS Networks.

- Compact and lightweight design
- Direct connection to MODBUS Network
- Up to 128 indoor units can be controlled in one MODBUS Convertor
- The MODBUS Convertor permits central monitoring and control of air conditioners from BMS or Central Controller

Functions



Specifications

Model name	UTY-VMGX	
Power supply	220-240V 50/60Hz, Single phase	
Input power	W	Max. 2
Dimensions (H x W x D)	mm	54 × 260 × 150
Weight	g	1,100



Network Convertor

UTY-VTGX (DC power supply type)

The Network Convertor offers a total solution for multiple air conditioning systems to be controlled.

Max. controllable
16
single indoor units

Max. controllable
100
Network Convertors




Functions


Solutions for multiple air conditioning systems

- The convertor is required when connecting single units to a VRF network system
- Administrator can perform total management of single units with a centralised VRF controller

Single unit with VRF



Single split type unit management




Max indoor units connected by one convertor: 16

Solutions for easy installation

DC power supply type can be powered by indoor unit. No power supply construction for convertor.

Easy wiring




The new convertor is light weight and compact reducing the installation space required.

Design flexibility

Size
85% REDUCTION

Weight
250 g




Specifications

Model name	UTY-VTGX	
Power supply	polar 3 wire DC12V	non polar 2 wire DC12V
Input power	W	Max. 1.2
Dimensions (H x W x D)	mm	43 × 117 × 140
Weight	g	250

KNX® Convertor (for VRF)

Max. controllable
128
indoor units

Max. controllable
100
outdoor units




UTY-VKGX

It is possible to control the VRF system from a central / home controller via KNX network.

- The new KNX Convertor enables connection of the central / home controller and FG VRF system
- A maximum of 128 indoor units and 100 outdoor units can be connected to a single KNX Convertor

Functions




Specifications

Model name	UTY-VKGX	
Power supply	220-240V 50/60Hz	
Input power	W	1.5
Dimensions (H x W x D)	mm	54 × 260 × 150
Weight	g	1,200

Network Convertor

Max. controllable
16
Single indoor units

Max. controllable
4
Group Remote Controllers




UTY-VGGXZ1

- This Network Convertor used for connecting single split systems to the VRF network system


Functions

Used for connecting single split systems to the VRF network

- Split type systems can be centrally controlled from a central controller or System Controller with connection to the VRF via a network convertor
- ON / OFF Control, Master control, Room temperature and Fan speed setting via the Network Convertor are available
- One Network Convertor can be used to connect and control up to 16 single units



Please consult your distributor for connectable split type air conditioners. Up to 100 Network Convertors may be connected in a single VRF network system. One Network Convertor is considered as a single refrigerant system, irrespective of the number of connected single models.



External Switch Controller

UTY-TEKX

Air conditioner settings switching can be controlled by connecting additional sensor switches

- In combination with a field supplied card key switch or other sensor, the External Switch Controller allows control of the ON / OFF, room temperature, fan speed and master control functions. This makes this product suitable for installations in hotel rooms
- Card key or other sensor switches are available as a field supplied parts





Functions

Installation example


Auto mode operation, which switches the cooling and the heating automatically, is enabled by using the sensor switch and external switch controller.

Note: All indoor units will operate in the same mode.



Note 1. Please choose a thermosensor switch which can be set up for T1 and T2.
Note 2. The remote controller's operation is prior to the auto mode operation.

Electrical wiring



Specifications

Model name	UTY-TEKX	
Power supply	DC 12V	
Dimensions (H x W x D)	mm	120 x 75 x 30
Weight	g	100


DC12V is supplied by indoor unit.

Signal Amplifier

UTY-VSGXZ1


- Transmission line length can be extended up to 3,600m with multiple signal amplifiers
- Up to 40 signal amplifiers can be installed in a VRF network system
- A signal amplifier is required:-

- (1) When the total wiring length of the transmission line exceeds 500m
- (2) When the total number of units on the transmission line exceeds 64




Functions

Installation example



Specifications

Model name	UTY-VSGXZ1	
Power supply	208-240V 50/60Hz, Single phase	
Input power	W	4.5
Dimensions (H x W x D)	mm	67 x 288 x 211
Weight	g	1,500





EFFECTIVE HEAT EXCHANGE AND SIMULTANEOUS FRESH AIR VENTILATION

High efficiency and low noise levels are achieved by using a highly efficient heat exchange process. A comfortable air conditioned space is created by conveniently selecting whether to use heat exchange or normal ventilation setting according to the requirements of the conditioned space.

VENTILATION

Energy Recovery Ventilator Outdoor Air Unit

Energy Recovery Ventilator Range

Airflow rate (m ³ /h)	250	350	500	800	1000
Model code	025	035	050	080	100
Energy Recovery Ventilator	NEW  UTZ-BD025C	NEW  UTZ-BD035C	NEW  UTZ-BD050C	NEW  UTZ-BD080C	NEW  UTZ-BD100C

Outdoor Air Unit Range

Airflow rate (m ³ /h)	1080	1680	2100
Model code	054	072	096
Outdoor Air Unit	 ARXH054GTAH	 ARXH072GTAH	 ARXH096GTAH

Energy Recovery Ventilator

Models

- UTZ-BD025C **NEW**
- UTZ-BD035C **NEW**
- UTZ-BD050C **NEW**
- UTZ-BD080C **NEW**
- UTZ-BD100C **NEW**



Features

Heat exchange ventilation and normal ventilation


Heat exchange ventilation

When a room is cooled or heated, the exhausted cooling / heating energy is recovered through heat exchange ventilation.

Normal ventilation

The operation is used during periods when the room space requires no cooling or heating effect, i.e. when there is minimal temperature difference between the indoor and outdoor environments.

Adopts a highly efficient counter flow heat exchange element




Energy efficiency and ecology

Energy consumption is dramatically reduced by using a counterflow heat exchange element. The air conditioning load is reduced by approximately 20%, resulting in significant energy savings and recovers up to 77% of the heat in the outgoing air.

Energy saving
20%

Features of the heat exchange element

With the cross-flow element, air moves in a straight line across the element. With the counter-flow element, air flows through the element for a longer time (longer distance), so the heat exchange effect remains unchanged.



Quiet operation

Significantly reducing low pressure loss and noise allows low noise operation.

Slim shape and easier installation

A counter flow heat exchange element is used for reduced noise and a slimmer, more compact body shape.



Improved Static Pressure

Static pressure is improved by adopting a powerful fan motor allowing use for these units in a wide variety of building types.

Easy remote operation



- Power: ON / OFF
- Air volume: High/Low
- Heat exchange / Normal ventilation
- ON / OFF Timer
- Clean filter display

Specifications

		(Tentative)						
Rated flow rate		250 m³/h	350 m³/h	500 m³/h	800 m³/h	1000 m³/h		
Model name		UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C		
Power source		220 - 240V, 50Hz						
HEAT EXCHANGE VENTILATION	Input power	Extra high / High / Low	W	128 / 123 / 96	190 / 185 / 168	289 / 225 / 185	418 / 378 / 295	464 / 432 / 311
	Air flow rate	Extra high / High / Low	m³/h	250 / 250 / 190	350 / 350 / 240	500 / 500 / 440	800 / 800 / 630	1000 / 1000 / 700
	External static pressure	Extra high / High / Low	Pa	105 / 95 / 45	140 / 60 / 45	120 / 60 / 35	140 / 110 / 55	105 / 80 / 75
	Temperature exchange efficiency	Extra high / High / Low	%	75 / 75 / 77	75 / 75 / 78	75 / 75 / 76	75 / 75 / 76	75 / 75 / 79
	Energy exchange efficiency cooling	Extra high / High / Low	%	63 / 63 / 65	66 / 66 / 71	62 / 62 / 64	65 / 65 / 68	65 / 65 / 70
NORMAL VENTILATION	Energy exchange efficiency heating	Extra high / High / Low	%	70 / 70 / 72	69 / 69 / 73	67 / 67 / 69	71 / 71 / 74	71 / 71 / 76
	Sound pressure level	Extra high / High / Low	dB*	31.5 / 30.5 / 26.5	33.0 / 31.0 / 25.5	37.5 / 35.5 / 32.5	37.5 / 37.0 / 34.5	38.5 / 37.5 / 34.5
	Input power	Extra high / High / Low	W	128 / 123 / 96	190 / 185 / 175	289 / 225 / 185	418 / 378 / 295	464 / 432 / 311
	Air flow rate	Extra high / High / Low	m³/h	250 / 250 / 190	350 / 350 / 240	500 / 500 / 440	800 / 800 / 630	1000 / 1000 / 700
	External static pressure	Extra high / High / Low	Pa	105 / 95 / 45	140 / 60 / 45	120 / 60 / 35	140 / 110 / 55	105 / 80 / 75
Sound pressure level	Extra high / High / Low	dB*	31.5 / 30.5 / 26.5	33.0 / 31.0 / 25.5	38.5 / 38.0 / 32.5	37.5 / 37.0 / 34.5	40.5 / 39.5 / 36.5	
Dimensions (W × D × H)	mm			882 × 599 × 270	1050 × 804 × 317	1090 × 904 × 317	1322 × 884 × 388	1322 × 1134 × 388
Weight	kg			29	49	57	71	83
Outlet duct diameter	mm			150	150	200	250	250
Operation range	°C			-10 to 40				
Maximum humidity	%			85	85	85	85	85

* The noise level must be measured 1.5m below the centre of the unit.


Reverse mountable direct air supply / exhaust system

Adoption of straight air supply / exhaust system:


The duct design is simplified because the air supply / exhaust ducts are straight.

Since each unit can be mounted in the reverse position, only one inspection hole is needed for two units:

Two units can share one inspection hole so duct work is easier and more flexible.



Dimensions (Unit: mm)



	UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C
A	810	978	1018	1250	1250
B	599	804	904	884	1134
C	315	580	640	428	678
D	142	112	132	228	228
E	600	600	600	600	600
F	655	860	960	940	1190
G	19	19	19	19	19
H	270	317	317	388	388
I	135	159	159	194	194
J	159	182	182	218	218
K	882	1050	1090	1322	1322
L	414	470	470	612	612
M	95	70	70	85	85
N	Ø164	Ø164	Ø210	Ø258	Ø258
O	Ø144	Ø144	Ø194	Ø242	Ø242

Outdoor Air Unit

Models

ARXH054GTAH
ARXH072GTAH
ARXH096GTAH





Features

One VRF system can provide air conditioning and air supply at the same time

An outdoor air unit can be connected in the same VRF*1 system as the indoor units and can create fresh and comfortable air supply together through our highly advanced technology.

*1. Connectable VRF series: J-IIS, J-III, V-II, V-III, J-IIIIL and VR-II
OAU is prohibit to connect under the ambient temperature of 40°C or higher.



* Make sure the connected capacity is within the range of 50% to 100% of the outdoor unit capacity. In addition, if there are mixed connections with indoor units, the Outdoor Air Unit connection capacity becomes 30% or less of the outdoor unit capacity.


High energy savings and flexible duct design by using a DC motor

- Greatly reduces electricity consumption by adopting a permanent magnet compared to when using an AC motor




- Compared with an AC motor, changing the fan speed makes it possible to respond with flexibility to the external static pressure from 50 Pa to 240 Pa. Even when the damper equipment is not used, the static pressure can be adjusted and duct design is made easy

- Static pressure can be set easily using wired remote controller



Compact design

- A lightweight compact design at just 425 mm in height and 55 kg in weight for ARXH072 type. This unit can be installed easily even within a narrow space.



Various controllers

A variety of optional controllers are available, such as individual controllers, central controllers and building management controllers.

Individual Controllers



Central Controllers



* The temperature setting is discharged air temperature setting. The air volume is set to a constant speed.

Specifications

Rated flow rate		1000 m ³ /h	1500 m ³ /h	2000 m ³ /h
Model name		ARXH054GTAH	ARXH072GTAH	ARXH096GTAH
Power source	V/Ø/Hz	230/1/50		
Capacity	Cooling	kW	14.0	22.4
	Heating	kW	8.9	13.9
Input power	Cooling	W	179	292
	Heating	W	179	292
Airflow rate	m ³ /h	1,080	1,680	2,100
Static pressure	Standard (range)	Pa	185 (50-185)	200 (50-200)
		Pa	42	44
Sound pressure level	dB(A)	42	44	47
Dimensions (H × W × D)	mm	425 × 1,367 × 572	425 × 1,367 × 572	450 × 1,583 × 700
Weight		kg	48	55
		kg	5.52	12.70
Connection pipe diameter	Small	mm	9.52	12.70
	Large	mm	19.05	22.22
Operation range	Cooling	°CDB	5 to 43	5 to 43
	Heating	°CDB	-7 to 21	-7 to 21
Refrigerant		R410A	R410A	R410A

Note: Specifications are based on the following conditions.

Cooling: Outdoor temperature of 33°CDB / 28°CWB.

Heating: Outdoor temperature of 0°CDB / -2.9°CWB.


Pipe length: 7.5m Voltage: 240V.

Dimensions (Unit: mm)

Model: ARXH054

Model: ARXH072


Model: ARXH096



AIRSTAGE™ OPTIONS

Auto Louver Grille Kit (option)

Models
 UTD-GXTA-W
 UTD-GXTB-W
 UTD-GXTC-W



Features

Flexible Control

Operation with indoor unit


The Auto Louver can be operated via the remote controller of the indoor unit.

Up and down auto swing


- Auto airflow direction and auto swing
- 4 steps selectable

Auto closing louver

When the operation of the indoor unit is stopped, the louver will automatically close.



Dimensions



Model Name	Unit: mm					
	W1	W2	H1	H2	D1	D2
UTD-GXTA-W	683	645	180	148	9	84
UTD-GXTB-W	883	845				
UTD-GXTC-W	1,083	1,045				

Specifications

Model name		UTD-GXTA-W	UTD-GXTB-W	UTD-GXTC-W
Applicable indoor units		ARXD07/09/12/14GALH ARXK07/09/12/14GCLH	ARXD18GALH ARXK18GCLH	ARXD24GALH ARXK24GCLH
Power source		Connecting with control box of indoor unit		
Fixing of auto louver grille		Screw fixing to flange or square duct		
Extension square duct limit		1.0m (Max. duct length between indoor unit and grille)		
Dimensions (H × W × D)		mm	180 × 683 × (84+9)	180 × 883 × (84+9)
Weight	Net	kg	2.0	2.5
	Gross	kg	3.0	3.5
Color		White		
Louver motor		Stepping motor		
Accessories		Fitting frame, etc.		
Operation range	Cooling	°C	18 to 32	
		% RH	80% or less	
	Heating	°C	16 to 30	

* The Auto Louver Grille Kit can also be installed to ARXD07/09/12/14/18/24LATH revision code B models. Please refer to the Design & Technical manual for "revision code" details.

OPTIONAL PARTS LIST

Controllers / Interface

Type	Indoor Unit																		
	Cassette					Duct				Floor		Wall Mounted							
	4-way Compact	4-way		Circular Flow		Mini (With drain pump)	Slim (With drain pump)	Medium Static Pressure	High Static Pressure	—	EEV external	—	EEV external	—	—	—	—		
AUXB 07/09/12/14/18/24 GALH	AUXD 18/24 GALH	AUXA 18/24/30/34/36/45/54GALH	AUXM 018/024/030GLAH	AUXK 018/024/030/034/036/045/054GLAH	ARXX 07/09/12/14/18/24 GCLH	ARXD 07/09/12/14/18/24 GALH	ARXA 24/30/36/45 GBLH	ARXC36 GBTH, ARXC 36/45/60 GATH	ARXC 72/90/96 GATH	AGYA 007/009/012/014 GCAH	AGYE 007/009/012/014 GCAH	ABYA 12/14/18/24 GATH	ABYA 30/36/45/54 GATH	ASYA 007/009 GTAH	ASYE 007/009 GTAH	ASYA 012/014 GCAH	ASYE 012/014 GCAH	ASYA 18/24 GBCH	ASYA 030/034 GTAH
Wired Remote Controller	● UTY-RNRVZ2																		
	● UTY-RNKYT																		
Simple Remote Controller	● UTY-RSRY, UTY-RHRY																		
Wireless Remote Controller	● UTY-LNHY																		
Central Remote Controller	● UTY-DCGY																		
Touch Panel Controller	● UTY-DTGYZ1																		
System Controller, System Controller Lite	● UTY-APGXZ1, UTY-ALGXZ1																		
BACnet Gateway	● UTY-ABGXZ1, UTY-VBGX																		
Network Converter for LonWorks	● UTY-VLGX																		
MODBUS Converter	● UTY-VMGX	● UTY-VMGX		● UTY-VMGX		● UTY-VMSX UTY-VMGX		● UTY-VMGX		● UTY-VMSX UTY-VMGX		● UTY-VMGX	● UTY-VMGX	● UTY-VMSX UTY-VMGX		● UTY-VMGX	● UTY-VMGX		
KNX Converter	● UTY-VKGX	● UTY-VKSX UTY-VKGX		● UTY-VKGX		● UTY-VKSX UTY-VKGX		● UTY-VKGX		● UTY-VKSX UTY-VKGX		● UTY-VKGX	● UTY-VKGX	● UTY-VKSX UTY-VKGX		● UTY-VKGX	● UTY-VKGX		
External Switch Controller	● UTY-TEKX																		

Others

Type	Indoor Unit																		
	Cassette					Duct				Floor		Wall Mounted							
	4-way Compact	4-way		Circular Flow		Mini (With drain pump)	Slim (With drain pump)	Medium Static Pressure	High Static Pressure	—	EEV external	—	EEV external	—	—	—	—		
AUXB 07/09/12/14/18/24 GALH	AUXD 18/24 GALH	AUXA 18/24/30/34/36/45/54GALH	AUXM 018/024/030GLAH	AUXK 018/024/030/034/036/045/054GLAH	ARXX 07/09/12/14/18/24 GCLH	ARXD 07/09/12/14/18/24 GALH	ARXA 24/30/36/45 GBLH	ARXC36 GBTH, ARXC 36/45/60 GATH	ARXC 72/90/96 GATH	AGYA 007/009/012/014 GCAH	AGYE 007/009/012/014 GCAH	ABYA 12/14/18/24 GATH	ABYA 30/36/45/54 GATH	ASYA 007/009 GTAH	ASYE 007/009 GTAH	ASYA 012/014 GCAH	ASYE 012/014 GCAH	ASYA 18/24 GBCH	ASYA 030/034 GTAH
IR Receiver Unit	● UTY-LRHYB1		● UTY-LBHDX		● UTB-TWC														
Human Sensor Kit	● UTY-SHZXC																		
Remote Sensor Unit	● UTY-XSZX																		
Cassette Grille	● UTG-UFYD-W	● UTG-UGYA-W		● UTG-UKYC-W															
Auto Louver Grille Kit	● UTD-GXTA-W ● UTD-GXTB-W(18) ● UTD-GXTC-W(24)																		
Long Life Filter	● UTD-LF25NA ● UTD-LF60KA																		
Flange	● UTD-SFD4ST UTD-RF204 ● UTD-RF204																		
Drain Pump Unit	● UTZ-PX1NBA ● UTR-DPB24T																		
Wide Panel	● UTG-AKXA-W		● UTG-AGYA-W		● UTG-AKXA-W														
Panel Spacer	● UTG-BKXA-W		● UTG-BGYA-W		● UTG-BKXA-W														
Fresh Air Intake Kit	● UTZ-VXAA	● UTZ-VXRA		● UTZ-VXRA															
Air Outlet Shutter Plate	● UTR-YDZB	● UTR-YDZK		● UTR-YDZK															
Insulation for High Humidity	● UTZ-KXGC	● UTZ-KXRA	● UTZ-KXRA		● UTZ-KXRA														
Half Concealed Kit	● UTR-STA																		

OPTIONAL PARTS

Controllers

For Individual Control



<p>Wired Remote Controller (Touch Panel) UTY-RNRYZ2</p> 	<p>Wired Remote Controller UTY-RNKYT</p> 	<p>Simple Remote Controller UTY-RSRY With operation mode</p> 
<p>Simple Remote Controller UTY-RHRY Without operation mode</p> 	<p>Wireless Remote Controller UTY-LNHY</p> 	<p>IR Receiver Unit UTB-TWC For ducted types</p> 
<p>IR Receiver Unit UTY-LRHYB1 For Cassette type</p> 	<p>Human Sensor Kit NEW UTY-SHZXC For Circular Flow Cassette type</p> 	

For Centralised Control



<p>Central Remote Controller UTY-DCGY</p> 	<p>Touch Panel Controller UTY-DTGYZ1</p> <p>Option UTY-PTGXA</p> 
<p>System Controller Lite Software UTY-ALGXZ1</p> <p>Option UTY-PLGXR2 UTY-PLGXA2 UTY-PLGXE2 UTY-PLGXX2</p> 	<p>System Controller Software UTY-APGXZ1</p> <p>Option UTY-PEGXZ1</p> 

Converters / Adaptors

For External Device


<p>BACnet® Gateway UTY-ABGXZ1 Software</p>  <p>WHITE-USB-KEY (Software Protection Key)</p>	<p>BACnet® Gateway NEW UTY-VBGX Hardware</p> 	<p>Network Converter for LonWORKS® UTY-VLGX</p> 
<p>MODBUS® Converter for VRF UTY-VMGX</p> 	<p>KNX® Converter for VRF UTY-VKGX</p> 	

For System Expansion

<p>Network Converter for single split systems UTY-VTGX DC power supply type</p> 	<p>Network Converter UTY-VGGXZ1</p> 	<p>External Switch Controller UTY-TEKX</p> 
<p>Signal Amplifier UTY-VSGXZ1</p> 		

Panels

For Cassette Type




<p>Cassette Grille UTG-UFYC-W For Compact Cassette type</p> 	<p>Cassette Grille UTG-UGYA-W For Cassette type</p> 	<p>Cassette Grille NEW UTY-UKYC-W For Circular Flow Cassette type</p> 
--	--	---

OPTIONAL PARTS

For Duct Type

<p>Flange (Round) UTD-RF204 For Medium Static Pressure Duct type / Ceiling type</p> 	<p>Flange (Square) UTD-SF045T For Medium Static Pressure Duct type</p> 	<p>Remote Sensor Unit UTY-XSZX For All Duct type</p> 
<p>Long-Life Filter UTD-LF25NA For Medium Static Pressure Duct type</p>  <p>UTD-LF60KA For High Static Pressure Duct type</p> 	<p>Auto Louver Grille Kit UTD-GXTA-W (for ARXD07/09/12/14, ARXK07/09/12/14) UTD-GXTB-W (for ARXD18, ARXK18) UTD-GXTC-W (for ARXD24, ARXK24) For Slim Duct type / Mini Duct type</p> 	<p>Drain Pump Unit UTZ-PX1NBA For Medium Static Pressure Duct type</p> 

For Cassette Type

<p>Wide Panel UTG-AKXA-W For Cassette type</p> 	<p>Panel Spacer UTG-BGYA-W For Cassette type</p> 	<p>Insulation Kit for High Humidity UTZ-KXRA For Cassette type UTZ-KXGC For Compact Cassette type</p> 
<p>Fresh Air Intake Kit UTZ-VXAA For Compact Cassette type</p>  <p>UTZ-VXRA For Cassette type</p> 	<p>Air Outlet Shutter Plate UTR-YDZB For Compact Cassette type Shuts the 4th outlet when installed in a 3 outlet directional air flow scenario.</p> 	<p>Air Outlet Shutter Plate UTR-YDZK For Cassette type Shuts the 4th outlet when installed in a 3 outlet directional air flow scenario.</p> 


For Ceiling Type

Drain Pump Unit
UTR-DPB24T
For Ceiling type



For Floor Type

Half Concealed Kit
NEW UTR-STA
For Floor type



Others

Communication system: External Connect Kit

<p>For Indoor unit</p> <p>UTY-XWZXZ7 </p> <p>UTY-XWZXZB </p> <p>UTY-XWZXZC </p>	<p>UTY-XWZXZD </p> <p>UTY-XWZXZE </p> <p>UTY-XWZXZF </p>	<p>For Outdoor unit</p> <p>UTY-XWZXZ6 </p> <p>UTY-XWZXZ9 </p> <p>UTY-XWZXZ8 </p>
<p>For RB unit</p> <p>UTY-XWZXZ6 </p> <p>UTY-XWZXZB </p>	<p>For Central Remote Controller</p> <p>UTY-XWZXZ7 </p> <p>UTY-XWZXZ8 </p> <p>UTY-XWZXZA </p>	<p>For Touch Panel Controller</p> <p>UTY-XWZXZA </p>

External Input and Output Function / External Connect Kit / Communication Kit

Type	Indoor unit						Outdoor unit		Controller		Other
	Cassette	Duct	Floor, Floor EEV external	Ceiling / Floor	Ceiling	Wall Mounted, Wall Mounted EEV external	VR-II	V-III	Central Remote Controller	Touch Panel Controller	RB Unit
Input Function	Operation / Stop					● UTY-XWZXZD ○ UTY-XWZXZB					
	All ON / All OFF								● UTY-XWZXZ7 ○ UTY-XWZXZ8	● *2 ○ *2	
	Batch Stop						● UTY-XWZXZ6				
	Forced Stop					● UTY-XWZXZD ○ UTY-XWZXZB					
	Emergency Stop					● UTY-XWZXZD ○ UTY-XWZXZB			● UTY-XWZXZ7 ○ UTY-XWZXZ8	● *2 ○ *2	
	Forced Thermostat Off					● UTY-XWZXZE ○ UTY-XWZXZ7					
	Low Noise Mode Operation						● UTY-XWZXZ6				
	Cooling / Heating Priority							● UTY-XWZXZ6			● UTY-XWZXZ6 ○ UTY-XWZXZB
	Outdoor Unit Operation Peak Control						● UTY-XWZXZ6				
	Power Usage Information from Electricity Meter							● UTY-XWZXZF			● *2 ○ *2
Output Function	Operation Status					● UTY-XWZXZC	○ UTY-XWZXZ6		○ UTY-XWZXZA		
	Error Status					● UTY-XWZXZC	○ UTY-XWZXZ6		○ UTY-XWZXZA		
	Indoor Unit Fan Operation Status					● UTY-XWZXZC					
	Auxiliary Heater Output		● UTY-XWZXZC								
	Base Heater							● UTY-XWZXZ9			

*2: Touch Panel Controller has these functions for Dry contact and Apply voltage, however, the above External Connect Kit is not necessary because Touch Panel Controller has an external input terminal block.

● : Dry Contact ○ : Apply Voltage

OPTIONAL PARTS

Connection Units

Separation Tube

<p>UTP-AX054A</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-AX090A</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-AX180A</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-AX567A</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 
<p>UTP-BX090A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-BX180A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-BX567A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 	

Header

<p>UTR-H0906L / UTR-H1806L</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTR-H0908L / UTR-H1808L</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-J0906A / UTP-J1806A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-J0908A / UTP-J1808A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 
---	---	--	---

Outdoor Unit Branch Kit

<p>UTP-CX567A</p> <p>Gas Pipe</p>  <p>Liquid Pipe</p> 	<p>UTP-DX567A</p> <p>Suction Gas Pipe</p>  <p>Discharge Gas Pipe</p>  <p>Liquid Pipe</p> 		
--	--	--	--

EV Kit

Model code ≤ 09 : UTR-EV09XB
 Model code ≥ 12 : UTR-EV14XB
 For Compact Wall Mounted type



RB Unit

Model code ≤ 09 : UTR-EV09XB
 Model code ≥ 12 : UTR-EV14XB
 For Compact Floor type



UTP-RX01AH / UTP-RX01BH /
 UTP-RX01CH
 Single type



UTP-RX04BH
 Multi type



Specifications

Separation Tube

Model name		UTP-AX054A	UTP-AX090A	UTP-AX180A	UTP-AX567A
Total cooling capacity of indoor unit	kW	19.6 or less	28.0 or less	28.1 to 56.0	56.1 or more
Model name		UTP-BX090A (for VR-II)		UTP-BX180A (for VR-II)	UTP-BX567A (for VR-II)
Total cooling capacity of indoor unit	kW	28.0 or less		28.1 to 56.0	56.1 or more

Header

Model name	3-6 Branches	UTR-H0906L	UTR-H1806L
	3-8 Branches	UTR-H0908L	UTR-H1808L
Total cooling capacity of indoor unit	kW	28.0 or less	28.1 to 56.0
Model name	3-6 Branches	UTP-J0906A (for VR-II)	UTP-J1806A (for VR-II)
	3-8 Branches	UTP-J0908A (for VR-II)	UTP-J1808A (for VR-II)
Total cooling capacity of indoor unit	kW	28.0 or less	28.1 to 56.0

Outdoor Unit Branch Kit

Model name		UTP-CX567A (for V-II)	UTP-DX567A (for VR-II)
Model name	2 outdoor units	1	
	3 outdoor units	2	

EV Kit

Model name	UTR-EV09XB		UTR-EV14XB	
Application model	ASYE004GTAH ASYE007GTAH ASYE009GTAH	AGYE004GCAH AGYE007GCAH AGYE009GCAH	ASYE012GCAH ASYE014GCAH	AGYE012GCAH AGYE014GCAH

RB Unit

Model name		Single type			Multi type
Number of outdoor units		UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX04BH
Power source	V/∅/Hz	230 / 1 / 50			
Input power	W	17	24	31	96
Number of branches		1	1	1	4
Maximum capacity of connectable indoor units(Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 56.0*1
Maximum capacity of connectable indoor units per branch(Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 18.0
Maximum number of connectable indoor units per branch		3	8	8	8
Dimensions (H × W × D)	mm	198 × 298 × 268	198 × 298 × 268	198 × 298 × 268	260 × 658 × 428

*1: In the case of two RB units connected in series (total 8-branches), the maximum capacity of connectable indoor units is up to 56.0kW.

ABOUT US

Since we began our air conditioning business in 1971, our products have been popular globally, and we continue to improve, evolve and expand our lineup to exceed customers' expectations.

OUR HISTORY

GLOBAL NETWORK

HIGH QUALITY DEVELOPMENT AND PRODUCTION

FACILITIES

PROJECT REFERENCES



OUR HISTORY

Fujitsu General's overseas air conditioning business has been in operation since 1971, with our VRF solutions being on the market since 2001.

Fujitsu General's VRF AIRSTAGE™ Series has been developed based on our air conditioning technology along with an ongoing significant investment in research and development. We offer a series of products suitable for large homes to large scale buildings to meet the various needs of the market.

For LARGE BUILDINGS

1936

Established as Yaou Shouten Ltd.

1971

Air conditioner exports to Middle East begin.

2001

10HP / Heat recovery and Heat pump



AIRSTAGE S

2003

10HP / Heat recovery 8, 10HP / Heat pump & Cooling



AIRSTAGE S

2007

8 to 42HP / Heat pump



AIRSTAGE V

2009

High efficiency and compact design model
Extensive lineup from 8HP to 48HP
in 2HP increments / Heat pump



AIRSTAGE V-II

2012

High efficiency and compact design model
8 to 48HP / Heat Recovery



AIRSTAGE VR-II

For SMALL BUILDINGS

2004

Small VRF series is released. 6HP / Heat pump



AIRSTAGE J

2011

High efficiency and small capacity model
4HP to 6HP / Heat pump



AIRSTAGE J-II

2014

High efficiency and compact design model
4HP to 6HP / Heat pump



AIRSTAGE J-IIS

AIRSTAGE J-III

High efficiency and compact design models
4HP to 6HP / Heat pump



NEW

AIRSTAGE J-III L

High efficiency and compact design models
10HP to 12HP / Heat pump



NEW

AIRSTAGE V-III

High efficiency and large capacity model.
Extensive lineup from 8HP to 48HP in 2HP increments / Heat pump



AIRSTAGE™ HISTORY

1936 Established as Yaou Shouten Ltd. - 2016

2017

1998

Certification acquisition of

ISO14001

1998: Fujitsu General (Shanghai) Co.,Ltd.
1999: Fujitsu General (Thailand) co.,Ltd.
2002: FGA (Thailand) Co.,Ltd.
2006: Fujitsu General Central Air-conditioner (Wuxi) co.,Ltd.

2004

New Product Initiatives
Fujitsu introduced inverter technology which used R410A refrigerant.



2006

RoHS Compliant
Restriction of Hazardous Substances (ROHS) is an EU directive on the restriction of the use of certain hazardous substances in all consumer electrical and electronic equipment.




2012

DC Inverter Compressors
Use of 100% inverter driven DC compressors.



GLOBAL NETWORK

Fujitsu General's air conditioning business has acquired a major share of the overseas market. We have many production and sales facilities overseas, and we continue to develop and sell products that are proven around the world due to their easy-to-use functionality, reliability and continually evolving technology.



Fujitsu General (Shanghai) Co., Ltd.



F.G.L.S. Electric Co., Ltd.



Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



FGA (Thailand) Co., Ltd.



Fujitsu General (Thailand) Co., Ltd.
Fujitsu General Engineering (Thailand) Co., Ltd.



TCFG Compressor (Thailand) Co.,Ltd.



R&D Center - Fujitsu General(Shanghai)



R&D Center - Fujitsu General Engineering(Thailand)



JAPAN Head Office
R&D Center and 60m Height Difference
Testing Tower

HIGH QUALITY DEVELOPMENT AND PRODUCTION FACILITIES

Fujitsu General is one of Japan's leading air conditioning manufacturers with an R&D Center in Japan. We aim to provide customers with high quality and performance tested products.

Advanced Research Facility and Equipment

Performance Testing	 <p>Air Volume Measurement Room Measures air volumes of the air conditioners from compact RAC models to VRF.</p>	 <p>Calorimeter Measures the cooling / heating capacity by measuring the inlet and outlet temperatures, humidity and air volume of the air conditioner.</p>	 <p>Silent Room Measures the operating sound characteristics of air conditioners within a purpose built room designed to acquire precise readings.</p>
Reliability Testing	 <p>Constant Temperature Room Evaluates the product performance in cooling / heating operation under the various temperature and humidity conditions.</p>	 <p>Practical Test Room Evaluates the air conditioners performance under actual installation conditions.</p>	 <p>Shower Test Room Evaluates the outdoor unit under adverse conditions to simulates conditions such as typhoons.</p>
Transportation & Handling	 <p>Compressibility Testing</p>	 <p>Vibration Testing</p>	

Testing Laboratory

Fujitsu General EMC Laboratory Limited



ACQUISITION OF ISO 9001 AND ISO 14001

Of the overseas production bases 5 companies have completed the acquisition of ISO 9001 and ISO 14001 individually. In 2012, 11 overseas sales subsidiaries acquired certification for ISO 14001.




High Product Quality Assurance

All Fujitsu General factories have acquired ISO 9001, and have built quality control systems that are uniform around the world within this, to ensure consistent and stringent quality inspections.

Receiving Inspection
Parts procurement requires a supplier's test report. European regulation RoHS inspection is also performed by a special test department in house.

Stringent product quality inspection
A stringent quality inspection is carried out at each stage of the production process. High quality is maintained by stringent checks through inspectors and repetitive ongoing inspection.



PROJECT REFERENCES

Our products are popular due to their high quality, energy saving functionality and design for easy installation. They have been utilised in a wide range of building types including high rise office buildings, retail, hotels, public facilities, schools, hospitals and residential applications.



LIGHT COMMERCIAL



Office in Europe



Shop in Europe




Hotel in U.S.A.

Fujitsu General's Products has been installed in over 50 countries worldwide.



Restaurant in Middle East



Hotel in Australia



COMMERCIAL



Office in Europe



Office in China



Factory in U.S.A.



RESIDENTIAL



Residential in Europe



Residential in Middle East



Residential in Europe



Residential in Oceania

SUPPORT

Our support offering methodology is focused on total support. From the stages of design, installation and commissioning through to after sales support.

AIRSTAGE™ SUPPORT

AIRSTAGE™ / RAC SUPPORT TOOL

QUICK SERVICE & MAINTENANCE

SERVICE TOOL

WEB MONITORING TOOL

Category	Information Material											Tool				
	Product Sales Training Material	Product Technical Training Material	Product News	Brochures	Feature Promotion Movie	Operating Manual	Design and Technical Manual	Certificate Data	2D CAD Data	3D CAD (Revit) Data	Installation Manual	Service Manual	Design Simulator (RAC, PAC, VRF)	CFD Simulation	Service Tool / Web Monitoring Tool	Mobile Technician
Product Training	•	•														
Product Information			•	•	•	•	•									
Technical Information						•	•									
Model Selection						•							•			
Design						•		•	•							
Verification													•			
Installation						•				•						
After Sales and Service												•			•	•



AIRSTAGE™ SUPPORT


Fujitsu General provides a variety of product and technical information to engineers and consultants. We also conduct new product research and design support activities. We provide a wide range of support to maintain high quality from design to installation.

Training

Fujitsu General has many training facilities around the world that regularly conduct specialised product, technical and service training. These research facilities also support the development of people to ensure high technical capability.

Features

- Designing AIRSTAGE™ Systems
- Control systems on site training



Head Office Training Center: Japan



Europe Training Center: Germany



Europe Training Center: U.K.



America Training Center: U.S.A.



China Training Center: China



Asia Training Center: Singapore



Middle East Training Center: UAE




Australia Training Centre: Sydney

Technical information

We provide information and tools that are useful for air conditioning system design, such as unit performance data and tools that make model selection and estimation easy.

Features

- Design and Technical Manual
- Model Selection and Estimation
- Certificate Data
- 2D/3D CAD Data



Product information

New product information is provided in the form of documents for every new model released. These can be downloaded from a private section of our website. To access this website, please contact your Fujitsu representative.

Features

- Product News
- Brochures and all Manuals
- Feature / Promotion Movie




Technical support

Technical support is provided at every stage from design to installation to assist in providing the most suitable air conditioning solution.

Features

- CFD Simulation
- Commissioning Support



CFD Simulation



Commissioning Support


AIRSTAGE™ / RAC SUPPORT TOOL

Put the charts and pens away and design your projects on your computer with ease using the Design Simulator. Everything from selecting indoor and outdoor units, allocating controls and optional parts to designing the piping and wiring systems is made easier using the program's built-in features. Once your project is designed, take advantage of the Export functions to easily get materials lists, product specifications, refrigerant calculations and more. You can even export to Word, Excel, or Acrobat formats and group the relevant CAD data for your project.

Design Simulator

Automatically create model selection information


- Each unit can be automatically set by entering the required performance, type, and temperature conditions for each indoor unit and then dragging and dropping into the outdoor unit.
- Piping and wiring diagrams can be created automatically and it is easy to set branches, grouping and options.
- The additional refrigerant charging amount is automatically calculated when the pipe length is entered.
- It is also easy to set the remote controller groups, central controller and converters.
- The equipment list including the equipment information is created automatically.



Output the format that matches the application


The information specific to your project can be exported in a number of industry standard file formats.

- Word format (rtf)(doc)
- Excel format (csv)
- Acrobat format (pdf)
- Auto CAD format (DXF)
- 2D Data (DXF)
- 3D Data (RFA)



Update your Design Simulator

The database can be easily updated online using Auto Update function through FTP.




BIM Building Information Modeling

Fujitsu General provides the Building Information Modeling (BIM) object models and content for our VRF systems and other products for architects, designers and contractors using Autodesk® Revit® technology from our Website and Autodesk® Seek Website etc.


3D and 2D product data

We provide 3D data for our products. 2D CAD design operations are supported and 2D display is also provided. The data can also be output in other formats, such as DXF and DWG, which are used by other design CAD design programs.




Installation limitation

The equipment installation limitation range is shown. Installation requirements, such as distance from the wall, are automatically displayed to make it easy to produce highly reliable design layouts.




Update your Design Simulator

Other information, such as symbols showing the airflow direction that are required for installation drawings, are built in and can be automatically reflected in 2D drawings. Installation drawings can be created easily.



Product specifications and link information


Contains the basic information required for air conditioner design, including unit size, capacity, input power, noise, and airflow rate. This data can be procured from the Fujitsu General Website, Design Simulator and Autodesk® Seek Website.



QUICK SERVICE AND MAINTENANCE

If an error should occur on a unit or system, there is an abundance of support tools such as trouble code display on the product, the VRF Service Tool allows checking of the detailed status for the entire system, and a remote monitoring tool that uses the internet meaning support, quick service and maintenance is available anywhere and at any time.

Mobile troubleshooting tool for iPhone and Android



We have released an app for troubleshooting compatible with the iPhone, iPod touch and other Apple products. This application is a troubleshooting tool for all Fujitsu General air conditioners (RAC/PAC, VRF)

It assists you in checking the air conditioners condition. Error code check, Troubleshooting and Sensor check information is available.




Easy maintenance and monitoring

Design for easy maintenance


The air conditioner operating status and trouble status are viewable on the 7 segment display of the outdoor unit PCB or on the remote controller screen. The unit status can be checked efficiently enabling a quick response.

- Operation mode status
- Discharge temperature / Pressure status
- Compressor operation indication
- Address / Type / Number of outdoor unit
- Error code


7-segment LED



Wired Remote Controller (Touch panel)




Wired Remote Controller



Error diagnosis with the Service Tool


The unit status details for the VRF system can be checked on a PC screen by connecting to the Service Tool. A quick analysis can be made. Viewable parameters include:

- Operation status / control
- Monitoring operating condition
- Monitoring sensor data
- Indication of trend graph
- Error history
- Indication of refrigerant circuit diagram
- Automatic operation check for refrigeration cycle



Remote monitoring

VRF system operating status and error status details can be constantly monitored over the internet.



SERVICE TOOL


Extensive monitoring and analysis functions for installation and maintenance

- Operation status can be checked and analysed to detect even the smallest abnormalities
- Storage of data containing system operation detail on a laptop allows further review off site
- Up to 400 indoor units (a single VRF network system) can be controlled and monitored for large scale buildings or hotels
- This software can be connected to any point of transmission line with USB adaptor (locally purchased)

* The saved data can be displayed offline. However, the data saved by the following model cannot be displayed.
 • UTR-YSTB/UTR-YSTC (Service Tool)
 • UTR-YMSA (Web Monitoring Tool)


Automatic operation check for refrigeration cycle

After product installation, an operation check can be performed automatically. Self diagnosis functionality automatically judges whether each sensor value is normal, saving time and workload. The diagnosis can also be output as a report.




Remote technical support and maintenance

On site the service tool's screen can be shared with support personnel in a remote location. When visiting a site for troubleshooting, operation status can be shared in real time making assistance easy. The online chat function helps to support on site staff.



Various trend graphs are displayable

Previously, only 3 graphs could be viewed simultaneously, now multiple graphs can be displayed on the new Service Tool depending on the requirements.



Personal computer system requirements

	UTY-ASGXZ1
Operating system	• Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8.1 Pro (32-bit or 64-bit) • Microsoft® Windows® 10 Pro (32-bit or 64-bit)
CPU	1 GHz or higher
Memory	• 1 GB or more (for Windows Vista®, Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit]) • 2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])
HDD	40 GB or more of free space
Display	1366 x 768 or higher resolution
Interface	• 2 USB ports - 1 USB port is required for software protection key connection - 1 USB port is required for Echelon® U10 USB Network Interface
Software	Internet Explorer® 11 or Microsoft Edge / Adobe® Reader® 9.0 or later

•Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

Name and shape	Quantity	Application
WHITE-USB-KEY (Software protection key)	1	Software protection key to be connected to USB port on the Service Tool-installed PC. These products run only on a PC with WibuKey.

•Personal computer that satisfies the following system requirements


WEB MONITORING TOOL

Product features

- Troubleshooting is performed by monitoring each air conditioning unit remotely during periodical system checks
- Error notification can be automatically transmitted to several locations using the internet *1
- Requires either a dedicated internet connection or public telephone line
- Identification of an error is possible via error warnings and equipment status information obtained from a remote location
- The system data can be downloaded remotely. This data can be viewed in the offline mode of the service tool
- The PC being used to monitor equipment isn't required to install special software as access is via a general web browser


*1: Use of internet mail system required.

Web Monitoring System



Support 4 VRF network systems

USB adaptor (max. 4 adaptors per PC) permitted, monitoring of up to 1,600 indoor units. Suitable for large scale buildings or hotels.



Personal computer system requirements

	UTY-AMGXZ1
Operating system	• Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8.1 Pro (32-bit or 64-bit) • Microsoft® Windows® 10 Pro (32-bit or 64-bit)
CPU	1 GHz or higher
Memory	• 1 GB or more (for Windows Vista®, Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit]) • 2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])
HDD	40 GB or more of free space
Display	1366 x 768 or higher resolution
Interface	• USB port (for 10 USB Network Interface Max.4, Software protection key) • Either of the following interface is required for remote connection: - Internet using LAN: Ethernet port is required
Software	Internet Explorer® 11 or Microsoft Edge / Adobe® Reader® 9.0 or later

•Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

Name and shape	Quantity	Application
WHITE-USB-KEY (Software protection key)	1	Software protection key to be connected to USB port on the Service Tool-installed PC. These products run only on a PC with WibuKey.

•Personal computer that satisfies the following system requirements

FUJITSU COMMUNITY

SPORTING CHANCE

Fujitsu General Australia is extremely proud to be a major sponsor of the Sporting Chance Cancer Foundation.

Established in 1996 by a number of high profile Australian sports men and women, including Fujitsu Generals' longstanding ambassador Mark Taylor, Sporting Chance is a not-for-profit organisation that helps provide home support and care to children with cancer.

To date, Fujitsu General has donated more than \$7M to this worthy cause, with a percentage of sales from Fujitsu's air conditioning units going towards the funding of outreach programs and exploring better ways to treat and overcome cancer.

This support has enabled the Sporting Chance Cancer Foundation to fund nurses across Australia allowing children to receive improved cancer care closer to home. This funding also allows for remote treatment and care for families, and considerably reduces the time spent travelling to and from the nearest hospital, which could be thousands of kilometres from home.

Sporting Chance initiatives allow families to spend more quality time at home together, while still having access to the correct care for their child.

Fujitsu General is dedicated to the ongoing support of the Sporting Chance Cancer Foundation and its commitment to improving the cancer care available for children, as well as research and new treatment developments.



FUJITSU GENERAL AUSTRALIA

ABN 55 001 229 554

A Subsidiary of FUJITSU GENERAL LIMITED

www.fujitsugeneral.com.au

HEAD OFFICE

NSW: Eastern Creek Drive, Eastern Creek NSW 2766 Ph: (02) 8822 2500 Fax: (02) 8822 2501

VIC/TAS: Suite 1, Building 2, Omnico Business Centre,
270 Ferntree Gully Road, Notting Hill VIC 3168 Ph: (03) 9543 5899 Fax: (03) 9543 8299

QLD: Level 1, 371 McArthur Avenue, Hamilton QLD 4007 Ph: (07) 3257 2800 Fax: (07) 3257 2184

SA/NT: 128A Rose Terrace, Wayville SA 5034 Ph: (08) 8172 1180 Fax: (08) 8172 1190

WA: Unit 1, 24 Gibberd Road, Balcatta WA 6021 Ph: (08) 9240 5877 Fax: (08) 9240 5866

For more information:

email contact@fujitsugeneral.com.au OR call 1300 882 201



ISO 9001 Certified number: 01 100 89394
ISO 14001 Certified number: 01 104 9245/01
Fujitsu General (Thailand) Co., Ltd.



ISO 9001 Certified number: 01 100 79269



ISO 14001 Certified number: CNB311153-UK
Fujitsu General (Shanghai) Co., Ltd.



ISO 9001 Certified number: 15914G100658AM
ISO 14001 Certified number: 15912E1002283M
Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



"**AIRSTAGE**" is a worldwide trademark of FUJITSU GENERAL LIMITED and is a registered trademark in Japan and other countries or areas.

- Specifications and design are subject to change without notice for future improvement.
- For further details, please check with our authorised dealer.
- iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries.
- Other company and product names mentioned herein may be registered trademarks, trademarks or trade names of their respective owners.

• Actual product colours may be different from the colours shown in this printed material.

Distributed by:

FUJITSU

FUJITSU GENERAL AUSTRALIA
ABN 55 001 229 554
A SUBSIDIARY OF FUJITSU GENERAL LIMITED
www.fujitsugeneral.com.au
EMAIL contact@fujitsugeneral.com.au
PHONE 1300 882 201